





LANDSCAPER (CAT I)

LANDSCAPING



ABOUT THE LANDSCAPER (CAT I) • CAT I Hitch

- Horsepower varies depending on model
- Serrated heat-treated grader blade
- Rear pulverizing roller
- Adjustable side wear plates
- 10" high by 9" deep box
- 3/8" side plates

Landscaper CAT I	P48	P60	P72	P84	P96
Dimensions (WLH)	49 X 38 X 33"	61 X 38 X 33"	73 X 38 X 33"	85 X 38 X 33"	97 X 38 X 33"
Working Width	48"	60"	72"	84"	96"
HP Req.	20-30	25-40	30-50	30-60	30-75
Hitch	CAT I	CAT I	CATI	CATI	CATI
Weight (lbs)	350	570	701	745	833
Weight w/ Harrow (lbs)	400	631	784	835	937
Weight w/ Harrow & Ripper (lbs)	525	774	954	1,005	1,170
Weight w/ Seeder Attach. (lbs)	460	690	750	945	1,500
Base Unit	\$3,432	\$3,870	\$4,224	\$4,950	\$5,736

Model Specific Options	Part Number	Price								
Harrow	H48	\$992	H60	\$1,133	H72	\$1,286	H84	\$1,380	H96	\$1,578
Ripper (CAT I)	RIP48	\$2,120	RIP60	\$2,130	RIP72	\$2,466	RIP78/84	\$2,550	RIP96	\$3,774
Grass Seeder	GS48	\$3,938	GS60	\$4,068	GS72	\$4,273	GS84	\$4,680	GS96	\$5,028
Brush	BR48	\$1,662	BR60	\$1,746	BR72	\$1,800	BR84	\$2,010	BR96	\$2,220
Smooth Roller	505548	\$872	505560	\$1,018	505572	\$1,081	505584	\$1,199	505596	\$1,373
Spike Rolling Harrow	SRH48	\$2,220	SRH60	\$2,388	SRH72	\$2,460	SRH84	\$2,730	SRH96	\$2,970

Universal Options	Part Number	Price
Board Scraper	LBS	\$885
Skid Steer to CAT I Quick Hitch Adapter Plate	CATIAP	\$1,085
Push/Pull Hitch	FMH	\$1,644
Push/Pull Hitch With Hydraulic Angling	PFMH	\$3,180
6"Hitch Extension Set (CAT I) Required if using Swivel Hitch on Landscaper	1000HE	\$642
Hydraulic Top Link (CAT I & CATII) 10" Stroke (20-1/4" Retracted)	НТС	\$385
Hydraulic Top Link (CAT II) 14" Stroke (24-1/4" Retracted)	HTC14	\$395
Ripper Cylinder 2" x 8"	20FEM08-NW	\$236
Harrow Cylinder 2" x 5"	CYL-S	\$372
CATI, 3PH, 22° Swivel Hitch	3PHSWL-CATI	\$2,424
Hose Kit With Male Pioneer Ends	H-KIT	\$183



LANDSCAPER (CAT II)

LANDSCAPING

Prices Effective as of 9-22

ABOUT THE LANDSCAPER (CAT II)

- CAT II Hitch
- 70-120 horsepower
- Serrated heat-treated grader blade
- Rear pulverizing roller
- Adjustable side wear plates
- 18" high by 17" deep box
- 1/2" side plates

Landscaper CAT II	P96H
Dimensions (WLH)	99 X 46 X 34"
Working Width	96"
HP Req.	70-120
Hitch	CAT II
Weight (lbs)	945
Weight w/ Harrow (lbs)	1,060
Weight w/ Harrow & Ripper (lbs)	1,260
Base Unit	\$7,290

Model Specific Options	Part Number	Price
Harrow	H96	\$1,578
Ripper (CAT II only)	RIP96H	\$3,774
Brush	BR96	\$2,220
Skid Steer to CAT II Quick Hitch Adapter Plate	CATIIAP	\$1,172
Spike Rolling Harrow	SRH96	\$3,475

Universal Options	Part Number	Price
Hydraulic Top Link (CAT II) 10" Stroke (20-1/4" Retracted)	HTC	\$385
Hydraulic Top Link (CAT II) 14" Stroke (24-1/4" Retracted)	HTC14	\$395
Ripper Cylinder 2" x 8"	20FEM08-NW	\$236
Harrow Cylinder 2" x 5"	CYL-S	\$372
Hose Kit With Male Pioneer Ends	H-KIT	\$183





LANDSCAPER

HARROW (AVAILABLE FOR CAT I & II)

- Hardened 5/8" square teeth spaced at 2 1/2"
- Removes trash on surface
- Mixes grass seed into soil with seeder attachment

• Manual ratchet jack to raise

• Makes a nice seed bed

00000 • Manual adjustment from 0-4" deep

HITCH ADAPTER, SKID STEER (PULL ONLY)

- Hitch adapter to attach to skid steer
- Pull only



HITCH ADAPTER, SKID STEER (PUSH AND PULL)

- Hitch adapter to attach to skid steer
- Ability to push and pull



HARROW CYLINDER

- Replaces manual ratchet jack to control ripper
- Tooth depth hydraulically



SMOOTH ROLLER

- Smooth flat finish on soil, sand or synthetic
- Equestrian footings
- Self-adjusting scraper bar
- Water can be added to roll



6" HITCH EXTENSIONS

• Extension for more clearance

HITCH ADAPTER, HYDRAULIC TILTING

- Hitch adapter to attach to skid steer, with hydraulic
- Controls for tilts
- Ability to push and pull



HYDRAULIC TOP LINK CYLINDER

- Top link grading control
- 8" stroke CAT I 0

PLEMENT

- 10" or 14" stroke CAT II
- Ball ends

GENERAL

DISTRIBUTORS


LANDSCAPER

GRASS SEEDER

48" (2.7 bushels),

- Quick attach two-pin mounting system
- · Seed rate adjustment with indicator
- Manual or optional hydraulic-controlled seed opener

• Available widths and capacity:



TILLER

- P.T.O. driven, 540 R.P.M.
- Available widths: 60" and 72"
- Self-resetting cam clutch to protect drive



RIPPER (AVAILABLE FOR CAT I & II)

- 1/2" thick x 2" wide bolt-on ripper teeth
- High-strength, stress-proof ripper bar
- Manual adjustment from 0 to 5" ripping depth
- Available widths: 48", 60", 72' 84" and 96"
- Manual ratchet jack to raise



REAR BRUSH (AVAILABLE FOR CAT I & II)

- Brushed finish on walking trails
- Break-away wings to smooth out side ridges
- Adjustable brush depth with two top wind jacks
- Available widths: 48", 60", 72", 84" and 96"



SWIVEL HITCH (AVAILABLE FOR CAT I & II)

- Turns 22 degrees each way
- Unique self-straightening feature when 3PH is raised
- Lock pin for hard surfaces
- Hitch extensions required



BOARD SCRAPER

- Get a nice finish from your machine even close to boards of arenas with the board scraper attachment
- Thick rubber to not damage boards

RIPPER CYLINDER

- Replaces manual ratchet jack to control ripper
- Adjust tooth depth hydraulically
- 2"x 8" Cylinder



SPIKED ROLLING HARROW

- Ideal for prepping seed beds
- For CAT I & II

DISTRIBUTORS

- Manual ratched jack adjustment
- To break up clumps

ERAL

EMENT



CAT I shown

AERASEEDER SELF PROPELLED

LANDSCAPING

Prices Effective as of 9-22

ABOUT THE AERASEEDER SELF PROPELLED

- Multi-spiked roller
- 850 perforations per square yard
- Honda engine with Eaton Hydrostatic Drive
- Rear smooth packing roller
- Cam-adjusted seed gate
- User-friendly controls
- Seed calibration tray

24" Self Propelled	AOSCS24SP	AOSCC24SP			
Dimensions (WLH)	33 X 60 X 37"				
Seeding Width	24"				
Front Roller	CONE	CONE			
Rear Roller	SMOOTH	CONE			
Weight (lbs)	400	455			
Seed Bin Capacity (Bushels)	1.25				
Base Unit	\$9,060	\$10,495			

Universal Options	Part Number	Price
Rear Spiked Roller	AOS-24CC	\$1,638
45-Pound Weight	45LBW	\$177
Weight Bracket	WB	\$106
8" D x 2" Wide Gauge Wheel Kit	AOS24GW-KIT	\$1,403
8" D x 4" Wide Gauge Wheels (Set of Wheels Only)	4X8GW	\$701





AERASEEDER SELF PROPELLED

8" DIAMETER X 2" WIDE GAUGE WHEEL KIT

- 2" wide x 8" diameter solid rubber wheels
- Adjustable stop to control depth of penetration on front spike roller



45-POUND WEIGHT

• Add weight to your product to enhance traction, compacting and even the weight distribution of your unit



REAR SPIKED ROLLER (SELF PROP. ONLY)

• Additional spiked roller increases perforations to 1,700 per square yard



8" DIAMETER X 4" WIDE GAUGE WHEEL

• Upgraded wheels compared to the 2" wide by 8" diameter gauge wheels



WEIGHT BRACKET (SELF PROP. ONLY)

• Holds up to six 45 pound weights





AERASEEDER 48" 72" & 96"

LANDSCAPING

Prices Effective as of 9-22

ABOUT THE AERASEEDER 48" 72" & 96"

- Internal agitator and bearing assembly deliver a smooth, constant seed flow
- The seed rate is achieved through an innovative locking knob adjustment control, allowing for maximum seed-spread accuracy
- The seed flow is turned on and off by a manual or hydraulic lever mechanism
- The tandem rollers oscillate 30 degrees on a pivot, allowing for consistent ground contact on rolling terrain





Aeraseeder	48"		72"		96"	
Dimensions (WLH)	52 X 36	δX21"	81 X 4	81 X 41 X 37"		1X37"
Seeding Width	44"		72"		96"	
Hitch	CATI		CATI		CAT I	
Weight (lbs)	460		1,185		1,400	
Seed Bin Capacity (Bushels)	4.75		12		16	
Front Cone and Rear Smooth	AOSCS48	\$10,209	AOSCS72	\$14,754	AOSCS96	\$18,887
Front Cone and Rear Cone	AOSCC48	\$11,670	AOSCC72	\$16,408	AOSCC96	\$20,776
Front Knife and Rear Smooth	AOSKS48	\$10,209	AOSKS72	\$14,754	AOSKS96	\$18,887
Front Knife and Rear Knife	AOSKK48	\$11,670	AOSKK72	\$16,408	AOSKK96	\$20,776

Model Specific Options	Part Number	Price	Part Number	Price	Part Number	Price
Toolbar Mount 3PH (For 2)	2AOS48TB	\$3,352	2AOS72TB	\$3,750	N/A	N/A
Toolbar Mount 3PH (For 3)	3AOS48TB	\$8,761	3AOS72TB	\$9,122	N/A	N/A
Rear Roller Ext. Kit	48RCSREXT	\$1,071	72RCSREXT	\$1,429	96RCSREXT	\$1,858
Manual Shut-off Kit	MSSSO	\$535	N/A	N/A	N/A	N/A
Tow Dolly	TD48	\$1,119	N/A	N/A	N/A	N/A



AERASEEDER 48" 72" & 96"

FRONT CONE & REAR SMOOTH

• Application: primary seeding & overseeding



FRONT KNIFE AND REAR KNIFE

Application: Overseeding & root slicing

• Plant grass seed directly into existing turf



TOW DOLLY (48" ONLY)

- Manual ratchet jack to raise and lower AeraSeeder on cart
- Cart attaches quickly to three-point hitch mounts on AeraSeeder



REAR SPIKED ROLLER EXTENSION (48,72, & 96)

- Extends rear-spiked roller and brush back
- 7" for optimum ground contact and smoother operation
- Stand-on platform for easy loading
 of hopper

FRONT CONE & REAR CONE

- Application: Overseeding
- Plant grass seed directly into existing turf, without tearing up the turf, or the soil
- Leave over 1,700 perforations per square yard



45-POUND WEIGHT

Suitcase style weight



MANUAL SEED SLIDE SHUT-OFF (48" ONLY)

- Comes standard with hydraulic shut off
- Manual shut off is for tractors without hydraulic remotes



TOOL BARS- TWO OR THREE AERASEEDERS (48 & 72 MODELS)

- CAT II Hitch
- Hydraulic control for seed slide opener

IMPLEMENT

DISTRIBUTORS



IN-FIELDER

LANDSCAPING

Prices Effective as of 9-22

ABOUT THE IN-FIELDER

- Heavy duty bolt-on serrated grader blade
- Floating clod-breaking pulverizer roller
- Heavy duty floating leveling bar
- Floating rear brush with side bumpers
- Broom and rake holders
- Adjustable rear brush
- Lubed pivots

IN-FIELDER D72

In-Fielder	D60	D72	D84	
Dimensions (WLH)	67 X 43 X 31"	80 X 48 X 32"	97 X 46 X 33"	
Width	60"	72"	84"	
Hitch	CAT I	CATI	CAT I & II	
Weight (Ibs)	620	835	935	
Pulverizer Roller	5"	5"	5"	
Packer Roller	1 PC. STEEL ROLL	6" X 12" UHMW ROLLS	6" X 12" UHMW ROLLS	
Base Unit	\$5,312	\$9,272	\$9,916	

IN-FIELDER D60

Model Specific Options	Part Number	Price	Part Number	Price	Part Number	Price
Rear Long Tine Rake Attachment	RLTR-60	\$1,187	RLTR-H-72	\$1,566	N/A	N/A
Rear Long Tine Rake Hydraulic	N/A	N/A	N/A	N/A	RLTR-84	\$2,261

Universal Options	Part Number	Price
50 gal. Water Tank, Pump, Switch & Nozzle	WT50G	\$1,786
Hand Wand Kit	HWK	\$233
Front Nozzle Kit w/ Switch & Pump	WTFN	\$1,017
Tow Kit w/ Wheels, Manual Lift w/ Ratchet Jacks (Not Rec. For Highway Use)	ITA	\$1,869
Tow Kit Extended for D72 with Harrow w/wheels, Manual lift w/ratchet	ITAEXAS	\$2,085
Rotary Sweeper Brush, 20" Dia. Hydraulic	RSB20	\$3,778
Electric Actuator 100mm Stroke	EAC100AS	\$1,455
Hydraulic Top Link (CAT II) 10" Stroke (20-1/4" Retracted)	HTC	\$385
Hydraulic Top Link (CAT II) 14" Stroke (24-1/4" Retracted)	HTC14	\$395
Hose Kit With Male Pioneer Ends	H-KIT	\$183
Sulky	SK117499	\$1,150
Edger	E105153	\$2,205





TOW KIT WITH WHEELS (D60 & D72)

• Tow kit to tow In-Fielder



ROTARY SWEEPER (ALL MODELS)

- 20" diameter nylon bristle brush with spring loaded break-away arm
- Hydraulic-driven
- Adjustable gauge wheel

• Prevent out field ridge

- Sweep material off grass and away from fence

HAND WAND KIT

• Hand wand kit for easy spraying



ELECTRIC ACTUATOR

• 100mm Stroke

TOW KIT EXTENDED (D72)

• Tow kit to tow D72 In-Fielder with long tine harrow option



WATER TANK (ALL MODELS)

- 50 gallon capacity
- 12V pump and rear nozzle



FRONT NOZZLE KIT

- For dust suppression
- Front nozzle, switch and pump



HYDRAULIC TOP LINK (CAT I & II)

- Available for CAT I & CAT II
- Available in 8", 10" and 14" stroke lengths



IN-FIELDER

REAR LONG TINE HARROW (D60)

- 14" long x 3/8" spring tines
- Loosen up hard-packed surfaces, which helps to dry the soil quicker



REAR LONG TINE HARROW HYDRAULIC (D84)

- 14" long x 3/8" spring tines
- Loosen up hard-packed surfaces, which helps to dry the soil quicker



SULKY

- Sulky fits between the UTV or ATV and the Infielder
- Required for UTVs or ATVs where the hitch moves with the suspension
- Keeps the Infielder level
- Sulky fits into a 2" receiver
- 21" wide x 20" long x 16" high
- 45 lbs weight





REAR LONG TINE HARROW (D72)

- 14" long x 3/8" spring tines
- Loosen up hard-packed surfaces, which helps to dry the soil quicker



EDGER

• Get the perfect edge



DRAG MAT

LANDSCAPING

Prices Effective as of 9-22

ABOUT THE DRAG MAT

- Rolls up behind your bumper to transport with unique crank, folding handle and lock system
- Fits on to any 2" trailer hitch receiver

Drag Mat	DM66	DM84		
Dimensions (WLH)	73 X 20 X 10"	91 X 20 X 10"		
Mesh Mat	1" SQ. STAINLESS STEEL MESH	1" SQ. STAINLESS STEEL MESH		
Base Unit	\$1,420	\$1,597		

Universal Options	Part Number	Price
Hitch Extension and Adapter	DMHEX	\$163

HITCH EXTENSION

• Often used for ATVs to move the Drag Mat up and away from wheels







LR30 LAWN ROLLER

LANDSCAPING

Prices Effective as of 9-22

ABOUT THE LAWN ROLLER

- Operates forward and reverse
- Unit Easily movable without starting the engine
- Powered by a 5.5 horsepower Honda gasoline engine
- Eaton hydrostatic transmission
- Power is delivered to the drum with a series sprockets, jack shaft and chains

Lawn Roller Self Propelled	LR30
Dimensions (WLH)	35 X 60 X 48"
Drum Diameter	30" X 24"
Weight lbs (Dry)	480
Weight lbs (w/ Water)	880
Lawn Roller	\$8,526

Universal Options	Part Number	Price
Checker Plate Roller Upgrade	117662	\$150
Ride on attachment	ROA	\$2,462



RIDE ON ATTACHMENT KIT

- Kit includes a pin on seat and roller allowing the operator to run the unit while seated.
- Ideal for large properties





ROTORAKE



ROTORAKE RR48

- Manual adjustment
- No tilt
- Wheel can be lifted in order to get up close to objects
- Dual-motor design delivers 40% more torque and eliminates outside bearings and chains



ROTORAKE RR60-RR84

- The RotoRake's hydraulic bidirectional rotor allows for operation in both directions
- Features a 25 degree angle and 28 degree tilt for easy swaling and ditching
- Dual-motor design delivers 40% more torque and eliminates outside bearings and chains



ROTORAKE P.T.O

- Power take-off for your RotoRake unit drives a pump which drives the rotor motors
- Features a 25 degree angle and 28 degree tilt for easy swaling and ditching
- Oscillating gauge wheels lock in level position for the (PTO) three point hitch use
- Dual-motor design delivers 40% more torque and eliminates outside bearings and chains

RotoRake	RR48-	R	RR4	RR48)	RR72	2	RR84		
Dimensions (WLH)	57 X 55 X	28"	.8" 57 X 55 X 28"		69 X 63 X 34"		81 X 63 X 34"		93 X 63 X 34"		
Working Width	48"		48"		60"		72"		84"		
Working Width (Angled 25°)	44"		44"		55"		65"		76"		
Weight (lbs)	725		725		1,150)	1,220)	1,280)	
Cont. PSI	3,000 M	AX	3,000 N	1AX	3,000 N	IAX	3,000 M	IAX	3,000 M	IAX	
PTO Required	N/A		N/A		N/A		N/A		N/A		
Roto Speed	230-450	RPM	230-450 RPM		230-450 RPM		230-450 RPM		230-450 RPM		
Hyd. GPM Range	18-30)	12-20	C	18-30		18-30		18-30		
Rotor Torque @ 2500 PSI	550 FT-l	BS	550 FT-	LBS	550 FT-I	550 FT-LBS		550 FT-LBS		550 FT-LBS	
Mount Type	MINI SKIDS (BOBC/	-	MINI SKID	STEER	STD. SKID:	STD. SKIDSTEER STD. SKIE		STEER	STD. SKIDS	STEER	
Gauge Wheels Included	1		1		2	2 2			2		
Tilt	N/A		N/A		MANU	MANUAL MAN		MANUAL		MANUAL	
Angle	MANU	AL	MANU	AL	MANUAL		MANUAL		MANUAL		
Base Unit	RR48-R	\$9,444	RR48	\$9,444	RR60	\$12,078	RR72	\$12,919	RR84	\$13,802	
Rotorake with Angle Kit*	N/A	-	N/A	-	RR60-RRAKHA	\$13,945	RR72-RRAKHA	\$14,786	RR84-RRAKHA	\$15,669	
Rotorake with Angle and Tilt Kit*	N/A	-	N/A	-	RR60-RRTKHA	\$14,945	RR72-RRTKHA	\$15,786	RR84-RRTKHA	\$16,669	
Rotorake with Angle and Tilt Kit (on the fly)*	N/A	-	N/A	-	RR60-RRHTAVK	\$16,236	RR72-RRHTAVK	\$17,076	RR84-RRHTAVK	\$17,960	
Foam Filled Tires (at time of order)	ADD	\$238	ADD	\$238	ADD	\$476	ADD	\$476	ADD	\$476	

Universal Options	Part Number	RR48-R	RR48	RR60	RR72	RR84
Angle Cylinder & Hose Kit (Used On tractor Remotes)	RRAK	N/A	N/A	\$420	\$420	\$420
Tilt Cylinder & Hose Kit (Used On tractor Remotes)	RRTK	N/A	N/A	\$420	\$420	\$420
12V Electric Valve & Hydraulic Cylinder Kit (Angle)*	RRAKHA	N/A	N/A	\$1,867	\$1,867	\$1,867
12V Electric Valve & Hydraulic Cylinder Kit (Tilt & Angle)*	RRTKHA	N/A	N/A	\$2,867	\$2,867	\$2,867
Rotorake with Angle and Tilt Kit (on the fly)*	RRHTAVK	N/A	N/A	\$4,158	\$4,158	\$4,158
CAT I & 2 3PH Plate	121933	N/A	N/A	\$800	\$800	\$800
RotoRake Side Cutters / Set	RRSCK	\$948	\$948	\$948	\$948	\$948
Foam Filled Tires	108110F	\$298	\$298	\$596	\$596	\$596

*WIRING KIT NOT INCLUDED



ROTORAKE WIRING KITS

Prices Effective as of 9-22

WIRING HARNESS



RotoRake Wiring Kits	Part Number	Price
ASV Skidsteers 8 Pin Wiring Kit (Deutsch Plug)	EWKD8CAT	\$402
Bobcat Skidsteers 14 Pin Wiring Kit (Deutsch Plug)	EWKD14BO	\$402
Bobcat Skidsteers 7 Pin Wiring Kit (Deutsch Plug)	EWKD7BO	\$1,177
Case Skidsteers 14 Pin Wiring Kit (Deutsch Plug)	EWKD14CNH	\$402
Caterpillar Skidsteers 14 Pin Wiring Kit (Deutsch Plug)	EWKD14CAT	\$402
Caterpillar Skidsteers 8 Pin Wiring Kit (Deutsch Plug)	EWKD8CAT	\$402
Gehl Skidsteers 14 Pin Wiring Kit (Deutsch Plug)	EWKD14CAT	\$402
JCB Skidsteers 14 Pin Wiring Kit (Deutsch Plug)	EWKD14JCB	\$402
John Deere 244J Loaders 14 Pin Wiring Kit (Deutsch Plug)	EWKD14JD	\$402
John Deere Skidsteers 14 Pin Wiring Kit (Deutsch Plug)	EWKD14JD	\$402
Kubota Skidsteers 14 Pin Wiring Kit (Deutsch Plug)	EWKD14KU	\$402
New Holland Skidsteers 14 Pin Wiring Kit (Deutsch Plug)	EWKD14CNH	\$402
Takeuchi Skidsteers 14 Pin Wiring Kit (Deutsch Plug)	EWKD14TA	\$402
Volvo Skidsteers 14 Pin Wiring Kit (Deutsch Plug)	EWKD14JCB	\$402
Wacker Neuson Skidsteers 14 Pin Wiring Kit (Deutsch Plug)	EWKD14KU	\$402
Terex Skidsteers 8 Pin	EWKD8CAT	\$402
Manual Toggle Switch with 12 Volt Cigarette Plug	RRMTS01	\$402


RotoRake Wiring Kits (RRHTAVK)	Part Number	Price
ASV 8 PIN	EWKV8CAT	\$596
BOBCAT 14 PIN	EWKV14BO	\$596
BOBCAT 7 PIN	EWKV7BO	\$2,055
CASE 14 PIN	EWKV14CNH	\$596
CAT 14 PIN	EWK14VCAT	\$596
CAT 8 PIN	EWKV8CAT	\$596
GEHL 14 PIN	EWKV14GEHL	\$596
JCB 14 PIN	EWKV14JCB	\$596
JOHN DEERE 14 PIN	EWKV14JD	\$596
KUBOTA 14 PIN	EWKV14KU	\$596
NEW HOLLAND 14 PIN	EWKV14NH	\$596
TAKEUCHI 14 PIN	EWK14VCAT	\$596
VOLVO 14 PIN	EWKV14JCB	\$596
WHACKER NEUSON	EWKV14WN	\$596
TEREX 8 PIN	EWKV8CAT	\$596
MANUAL TOGGLE	RRMTSV01	\$1,012



ROTORAKE

CAT I HITCH

CAT I hitch for your RotoRake



REMOTE-CONTROLLED HYDRAULIC KIT

- Hydraulic option for the RotoRake
- 12 volt Hydraulic valve option to tilt and angle
- You can choose one or both of these options



SIDE CUTTERS

• Pin on front or rear depending on desired direction of travel





MULTI-PACKER

LANDSCAPING

Prices Effective as of 9-22

ABOUT THE MULTI-PACKER

- Slots for optional ripper teeth
- Floating drum scraper
- 24" diameter steel drum
- Drum can be filled with water for increased compaction
- Storage stand
- Mounts for optional leveling blade
- CAT I and II Hitch



ANOTHER ANGLE OF MULTI-PACKER

Multi-Packer	MP36	MP48	MP60	MP72	MP84	MP96
Dimensions (WLH)	40 X 30 X 37"	52 X 30 X 37"	64 X 30 X 37"	76 X 30 X 37"	88 X 30 X 37"	100 X 30 X 37"
Working Width	36"	48"	60"	72"	80"	96"
Steel Drum Diameter	24"	24"	24"	24"	24"	24"
Weight lbs (Dry)	565	610	712	815	940	1,025
Weight Ibs (w/ Water)	960	1,190	1,460	1,765	1,930	2,300
Base Unit	\$4,299	\$4,572	\$4,880	\$5,270	\$5,716	\$6,433

Model Specific Options	Part Number	Price	Part Number	Price	Part Number	Price	Part Number	Price	Part Number	Price	Part Number	Price
Leveling Blade	MPLB36	\$899	MPLB48	\$918	MPLB60	\$1,014	MPLB72	\$1,116	MPLB84	\$1,250	MPLB96	\$1,371

Universal Options	Part Number	Price
Ripper Tooth	MG011	\$36
Ripper Shank	MG012	\$41
Replaceable Shank Tip- Chromium Carbon	GEN43	\$36
Replaceable Shank Tip- Chromium Carbon (Carbide Tip)	GEN43C	\$88
Tow Hitch/Draw Bar	MPTH	\$698





MULTI-PACKER

RIPPER TEETH

- Ripper teeth to rip up and soften ground
- Adjustable in 1" increments



тоw нітсн

• Add tow hitch to tow behind tractor or appropriate vehicle

LEVELING BLADE

• Redistributes and levels material



RIPPER TOOTH (MG011)

- Resistant to wear
- Replaceable tooth



RIPPER SHANK (MG012)

Resistant to wear





REPLACEABLE SHANK TIP

• Resistant to wear





TRAIL PRO

LANDSCAPING

Prices Effective as of 9-22

ABOUT THE TRAIL PRO

- Reclaim & reuse trail material
- Angled blades removes high spots and level the trail
- Spinning rotor pulverizes and separates root balls and stone dust
- Carbide-tipped teeth spins at 540 RPM
- Leveling plate made from ³/₄" wear resistant steel
- Unique edging disc (one on each side) removes grass and weeds from side of trail









ANOTHER ANGLE OF THE TRAIL PRO

TrailPro	TP50	TP60	TP72	TP96
Dimensions (WLH)	55 X 66 X 34"	67 X 66 X 34"	79 X 66 X 34"	103 X 66 X 34"
Working Width	50"	60"	72"	96"
Weight Ibs	1,250	1,475	1,600	1,900
Hitch	CATI	CAT I	CAT I	CAT II
Power	540 PTO	540 PTO	540 PTO	540 PTO
Base Unit (Hyd. Top Link Included)	\$22,591	\$22,943	\$23,267	\$29,232

Model Specific Options	Part Number	Price						
Rear Gauge Roller	TP50RR	\$2,108	TP60RR	\$2,169	TP72RR	\$2,229	TP96RR	\$2,449

REAR GAUGE ROLLER

• Packs down materials that cannot be drag-packed, such as wood chips and loose material





LANDSCAPING

IRON ANT

RENTAL / LANDSCAPING

Prices Effective as of 9-22

ABOUT THE IRON ANT

- Designed to move compactors plates onto truck then to desired location at the construction site
- Or move anything that can be lifted such as landscape rocks, tree balls, various building materials
- Requires two high torque cordless drills (NOT INLCUDED)

Iron Ant	IA30		
Capacity (lbs)	1,200		
Lifting Height	44"		
Lifting Width	30"		
Dimensions (WLH)	47.5 X 45 X 56.5"		
Unit Weight (lbs)	280		
Base Unit	\$4,995		

Options	Part Number	Price	
Pallet Fork Attachment	120594	\$502	

PALLET FORK ATTACHMENT

- Ideal attachment for lifting small pallets and other items designed for use with pallet forks.
- Lifting Capacity 600 lbs.
- Tine spacing 17" or 18" centers
- Tine height 2"
- Dimensions (WLH) 18 x 33 x 37"
- Unit weight 40 lbs.







LANDSCAPING

ROTORAKE PTO

LANDSCAPING

Prices Effective as of 9-22

ROTORAKE P.T.O

- Power take-off for your RotoRake unit drives a pump which drives the rotor motors
- Features a 25 degree angle and 28 degree tilt for
- easy swaling and ditching • Oscillating gauge wheels lock in level position for
- the (PTO) three point hitch use • Dual-motor design delivers 40% more torque and eliminates outside bearings and chains




RotoRake P.T.O	RR60PTO18G	RR72PTO18G	RR84PTO18G	
Dimensions (WLH)	69 X 63 X 34"	81 X 63 X 34"	93 X 63 X 34"	
Working Width	60"	72"	84"	
Working Width (Angled 25°)	55"	65"	76"	
Weight (lbs)	1,350	1,420	1,500	
Cont. PSI	3,000 MAX	3,000 MAX	3,000 MAX	
PTO Required	540RPM	540RPM	540RPM	
Roto Speed	230-450 RPM	230-450 RPM	230-450 RPM	
Hyd. GPM Range	18-30	18-30	18-30	
Rotor Torque @ 2500 PSI	550 FT-LBS	550 FT-LBS	550 FT-LBS	
Mount Type	3PH CAT 1 & 2	3PH CAT 1 & 2	3PH CAT 1 & 2	
Gauge Wheels Included	2	2	2	
Tilt	MANUAL	MANUAL	MANUAL	
Angle	HYDRAULIC	HYDRAULIC	HYDRAULIC	
Base Unit	\$15,773	\$17,824	\$19,480	
Foam Filled Tires (add to base)	\$476	\$476	\$476	

Universal Options	Part Number	RR60PTO18G	RR72PTO18G	RR84PTO18G
Tilt Cylinder & Hose Kit (Used On tractor Remotes)	RRTK	\$420	\$420	\$420
RotoRake Side Cutters / Set	RRSCK	\$948	\$948	\$948
Foam Filled Tires	108110F	\$596	\$596	\$596

SIDE CUTTERS

• Pin on front or rear depending on desired direction of travel



TILT CYLINDER & HOSE KIT

- Used on tractor remotes
- Requires a second set of remotes

FOAM FILLED TIRES

- Uses the same tire as air filled
- Weighs 39lbs (24 lbs heavier than air filled)

