



Worksaver



Hydraulic Post Drivers

Worksaver with over two decades of post driver innovations now offers two series of post drivers. Our standard duty model HPD-16 incorporates many of the innovations first brought to the market by Worksaver: “convertible” hydraulic valve, grease zerks at all major pivot locations, plated manual cranks, plastic slide blocks, adjustable legs, bubble level, and SplitCap™. The HPD-16 (32,000 lbs. of force) is ideal for the small property owner with limited fence posts to drive.

Our Q-series of hydraulic drivers, HPD-22Q (80,000 lbs. of force) and HPD-26Q (110,000 lbs. of force) offer ingenious solutions to routine maintenance to keep the operator building fence. Q-series drivers feature two time savings QuickChange™ system. Worksaver’s SplitCap™ with enhanced cylinder rod design allows the operator to perform routine maintenance on the rod cap seal without removing the cylinder from the driver. Our Q-spring assembly reduces spring change over from hours to minutes. This design offers increased service life when compared to conventional post driver springs. The integrated spring/spring-anchor design when mounted to the cushion mounts reduces vibration which further provides increased spring service life. Increasing fence-building performance, making the Q-series a game changer.

The Q-series of hydraulic post drivers continues Worksaver’s innovation with post drivers. In the past two decades Worksaver has brought the following enhancements to the market:

- First to replace metal rollers with plastic slide blocks
- Patented skid steer return lines on skid steer post drivers
- First to install a rubber deflector guard around driving head assembly
- Self-contain post driver for skid steer loaders
- First to develop front loader mounted post drivers
- First to develop “universal” return line fitting
- First with circular bubble level on all models
- First with adjustable legs on all models
- First with “convertible” valve for open center/closed center hydraulic systems



HPD-16/22Q Manual Adjust, 3-pt. Hydraulic Post Drivers



HPD-16

HPD-16/22Q

Manual Adjust, 3-pt. Hydraulic Post Drivers

The HPD-16/22Q models with manual adjust quickly delivers a tight post set for wood or steel posts. Base model offers manual adjustment cranks and bubble level for perfect vertical alignment on flatland or hillsides. Transport lock pin secures unit for travel and storage. Greaseable pivot points provide reliable movement of the driver.



Plated Manual Adjustment Cranks — Side-to-side and fore-aft post alignment. Plated manual cranks prevent rust and feature machined threads and grease zerks for quick, easy adjustment.




See it in action!



Post Holder — Spring loaded arm holds post securely for “hand free” operation.



Rubber Shield — First to install rubber shield around ram driving head, reduces flying wood chips and debris.



Bubble Level — First with a circular bubble level on all units for simple, yet accurate positioning of the driving ram.

WorkSaver Hydraulic Post Drivers

Worksaver



HPD-16/22Q/26Q SHC Hydraulic Adjust, 3-pt. Hydraulic Post Drivers

Designed and engineered for those who have serious fencing to do. These center mounted units offer all the quality features of the basic HPD-16 & HPD-22Q plus effortless hydraulic driver alignment controlled by two 3" x 6" hydraulic cylinders. For increased driving force, the heavy-duty HPD-26Q SHC delivers 110,000 lbs. of high-impact force for driving large posts in tough soil conditions. Big-foot stabilizer helps control tractor bounce on these larger units.

Maximum Post Sizes:

HPD-16SHC - 5" dia., 9' length

HPD-22Q SHC - 8-3/4" dia., 10' length

HPD-26Q SHC - 11" dia., 10' length



HPD-22Q SHC



BigFoot Stabilizer Leg — Standard on HPD-16/22Q/26Q SHC, Big-foot stabilizer provides sure footing for driving those larger posts, reducing the driving shock load to the tractor.



Q-Spring — Integrated spring anchors on Q-series drivers provide single bolt installation to cushion mounts resulting in easier spring replacement and increased service life of the spring. Spring life is increased over conventional springs with this patented design.



Reinforced Rails — Carriage reinforcement braces reduce carriage whip and insures durability of the driver.



Cushion Mount — Cushion mounts on Q-series drivers reduce spring vibration and driving ram shock resulting in increased reliability.



Quickchange™ System with SplitCap™ — Worksaver's patented Quickchange™ system with SplitCap™ and enhanced cylinder rod design for our HPD-series of post drivers. Allows the operator to perform routine maintenance on the rod cap seal without removing the ram from the mount. Saving hours of time and keeping the operator building fence.



Hydraulic Adjustable Mount — Hydraulic Adjustable mount with 3" x 6" cylinders provides superior ram control with trouble-free performance.



HPD-22Q SWO

HPD-16/22Q/26Q SWO

Offset 3-pt. Hydraulic Post Drivers

Driving post along existing fence lines, ditch banks, or corners is easily done with a SWO model. Hydraulic side shift extends the unit 24" to the left permitting the post driver to reach up to 46" left of the tractors center point. Heavy-duty 3-angle swivel mount pivots the driver 45°, 90° or rear facing for increased versatility. Slide tension adjusters provide easy extension of the unit, while providing support when extended. Two trailer hitch locations are standard.

HPD-16/22Q HFL

Front Loader Mounted, Hydraulic Post Drivers

Front loader mounted hydraulic adjust post drivers offer increased visibility and maneuverability for improved access in hard-to-reach areas. Available as either a HPD-16 or HPD-22Q these drivers can be position to the center or side of the loader for easier fence building. Choose from brackets with pin type mounting or select from our many interfacing quick attach brackets for most of today's popular loader brands.



Convenient control location



HPD-22Q HFL

Worksaver



Fast, Rugged & Versatile Hydraulic Post Drivers

HPD-16/22Q MSS/HSS, HPD-26Q HSS Skid Steer Mounted, Hydraulic Post Drivers

Want greater multi-task performance from your skid loader? Then connect it to a hydraulic skid steer mounted post driver. The HPD-16 & HPD-22Q are offered either with manual crank adjustment (MSS) or hydraulic adjustment (HSS) for quicker productivity. The model HPD-26Q HSS is all hydraulic adjust with 3" x 6" cylinders, all feature the Big-foot stabilizer for improved stability and operating performance. This combination makes transport simple, enables maneuverability into areas not accessible with a tractor while increasing operator productivity and skid steer versatility.



HPD-26Q HSS



Self-Contained Unit — Overhead view of compact design (required for select models of skid steers, available for all size drivers)



UHMW Polyethylene Slide Blocks — Used on all HPD-22Q/26Q drivers provide longer service life.



HPD-26Q HSS



HPD-16/22Q/26Q HSS/P Self-contained, Skid Steer Mounted, Hydraulic Post Drivers

Save time by simplifying driver installation and removal with a self-contained hydraulic post driver. These skid steer post drivers feature their own hydraulic pump, motor and reservoir. No special return line fittings are required with these units. Gear pump is used to move the oil within the self-contained system providing reliable operation. Note: Some skid steer models require the Self-contained post driver – check with your dealer.

Post Drivers Specifications


* UHMW Polyethylene Slide Blocks

Skid Steer Models should have SAE operating load capacity equal to or greater than 1.25 times post driver weight.



Model	HPD-16	HPD-16 SHC	HPD-16 HFL	HPD-16 MSS	HPD-16 HSS	HPD-16 HSS/P	HPD-16 SWO	HPD-22Q	HPD-22Q SHC
Max. Post Size	5" x 9'	5" x 9'	5" x 9'	5" x 9'	5" x 9'	5" x 9'	5" x 8'	8-3/4" x 10'	8-3/4" x 10'
Impact at Full Stroke	32,000 lbs.	32,000 lbs.	32,000 lbs.	32,000 lbs.	32,000 lbs.	32,000 lbs.	32,000 lbs.	80,000 lbs.	80,000 lbs.
Impact at Half Stroke	16,000 lbs.	16,000 lbs.	16,000 lbs.	16,000 lbs.	16,000 lbs.	16,000 lbs.	16,000 lbs.	40,000 lbs.	40,000 lbs.
Mount Type	3-pt. Cat I/II	3-pt. Cat I/II	Frt Loader	Skid Steer	Skid Steer	Skid Steer	3-pt. Cat I/II	3-pt. Cat I/II	3-pt. Cat I/II
Tilt Adj. Front/Back	10° each way	17° each way	17° each way	10° each way	17° each way	17° each way	17° each way	10° each way	17° each way
Tilt Adj. Side/Side	17° each way	20° each way	20° each way	17° each way	20° each way	20° each way	20° each way	17° each way	20° each way
Manual Adjust	Yes	No	No	Yes	No	No	No	Yes	No
Hydraulic Adjust	No	Yes	Yes	No	Yes	Yes	Yes	No	Yes
Adj. Cylinders/Size	N/A	(2) 3" x 6"	(2) 3" x 6"	N/A	(2) 3" x 6"	(2) 3" x 6"	(2) 3" x 6" (1) 2" x 24"	N/A	(2) 3" x 6"
Stabilizer Legs	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Big Foot	N/A	Yes	N/A	N/A	Yes	Yes	N/A	N/A	Yes
Slide Blocks Material	Nyrim	Nyrim	Nyrim	Nyrim	Nyrim	Nyrim	Nyrim	UHMW*	UHMW*
Spring Post Holder	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Min. Tractor Size	20-22 hp	20-22 hp	40-45 hp	N/A	N/A	N/A	40-45 hp	30-35 hp	30-35 hp
Rear Hitch Category	Cat. I or II	Cat. I or II	N/A	N/A	N/A	N/A	Cat. I or II	Cat. I or II	Cat. I or II
Min. Hydraulic Req.	3-4 GPM	3-4 GPM	3-4 GPM	3-4 GPM	3-4 GPM	10 GPM	3-4 GPM	6-8 GPM	6-8 GPM
QuickChange Rod Seal	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Q-springs	N/A	N/A	N/A	N/A	N/A	N/A	N/A	Yes	Yes
Valve(s)	Sgl. Spool	Sgl./Dbl. Spool	Sgl./Dbl. Spool	Sgl. Spool	Sgl./Dbl. Spool	Sgl./Dbl. Spool	Sgl./Trpl. Spool	Sgl. Spool	Sgl./Dbl. Spool
Hoses less couplers	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Offset (to left of tractor Ctr.)	N/A	N/A	N/A	N/A	N/A	N/A	46" Min	N/A	N/A
Self Contained Unit	N/A	N/A	N/A	N/A	N/A	Yes	N/A	N/A	N/A
Reservoir Capacity	N/A	N/A	N/A	N/A	N/A	5 Gallons	N/A	N/A	N/A
Pump Type	N/A	N/A	N/A	N/A	N/A	Gear	N/A	N/A	N/A
Pressure Relief Setting	N/A	N/A	N/A	N/A	N/A	2000 psi	N/A	N/A	N/A
Weight (lbs.)	600	875	1125	678	950	1283	1683	795	1035
Product Number	814400	814825	814835	814628	814630	815020	814855	815300	815330

Model	HPD-22Q-HFL	HPD-22Q MSS	HPD-22Q HSS	HPD-22Q HSS/P	HPD-22Q SWO	HPD-26Q SHC	HPD-26Q HSS	HPD-26Q HSS/P	HPD-26Q SWO
Max. Post Size	8-3/4" x 10'	8-3/4" x 10'	8-3/4" x 10'	8-3/4" x 10'	8-3/4" x 9'	11" x 10'	11" x 10'	11" x 10'	11" x 9'
Impact at Full Stroke	80,000 lbs.	80,000 lbs.	80,000 lbs.	80,000 lbs.	80,000 lbs.	110,000 lbs.	110,000 lbs.	110,000 lbs.	110,000 lbs.
Impact at Half Stroke	40,000 lbs.	40,000 lbs.	40,000 lbs.	40,000 lbs.	40,000 lbs.	55,000 lbs.	55,000 lbs.	55,000 lbs.	55,000 lbs.
Mount Type	Frt. Loader	Skid Steer	Skid Steer	Skid Steer	3-pt. Cat. I/II	3-pt Cat II	Skid Steer	Skid Steer	3-pt Cat. II
Tilt Adj. Front/Back	17° each way	10° each way	17° each way	17° each way	17° each way	17° each way	17° each way	17° each way	17° each way
Tilt Adj. Side/Side	20° each way	17° each way	20° each way	20° each way	20° each way	20° each way	20° each way	20° each way	20° each way
Manual Adjust	No	Yes	No	No	No	No	No	No	No
Hydraulic Adjust	Yes	No	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Adj. Cylinders/Size	(2) 3" x 6"	N/A	(2) 3" x 6"	(2) 3" x 6"	(2) 3" x 6" (1) 2" x 24"	(2) 3" x 6"	(2) 3" x 6"	(2) 3" x 6"	(2) 3" x 6" (1) 2" x 24"
Stabilizer Legs	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Big Foot	N/A	N/A	Yes	N/A	N/A	Yes	Yes	N/A	N/A
Slide Blocks Material	UHMW*	UHMW*	UHMW*	UHMW*	UHMW*	UHMW*	UHMW*	UHMW*	UHMW*
Spring Post Holder	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Min. Tractor Size	40-45 hp	N/A	N/A	N/A	40-45 hp	50-55 hp	N/A	N/A	50-55 hp
Rear Hitch Category	N/A	N/A	N/A	N/A	Cat. I or II	Cat. II	N/A	N/A	Cat. II
Min. Hydraulic Req.	6-8 GPM	6-8 GPM	6-8 GPM	10 GPM	6-8 GPM	12 GPM	12 GPM	12 GPM	12 GPM
QuickChange Rod Seal	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Q-springs	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Valve(s)	Sgl./Dbl. Spool	Sgl. Spool	Sgl./Dbl. Spool	Sgl./Dbl. Spool	Sgl./Trpl. Spool	Sgl./Dbl. Spool	Sgl./Dbl. Spool	Sgl./Dbl. Spool	Sgl./Trpl. Spool
Hoses less couplers	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Offset (to left of tractor Ctr.)	N/A	N/A	N/A	N/A	46" Min.	N/A	N/A	N/A	46" Min.
Self Contained Unit	N/A	N/A	N/A	Yes	N/A	N/A	N/A	Yes	N/A
Reservoir Capacity	N/A	N/A	N/A	5 Gallons	N/A	N/A	N/A	5 Gallons	N/A
Pump Type	N/A	N/A	N/A	Gear	N/A	N/A	N/A	Gear	N/A
Pressure Relief Setting	N/A	N/A	N/A	2000 psi	N/A	N/A	N/A	2000 psi	N/A
Weight (lbs.)	1275	828	1245	1385	1878	1215	1429	1575	2194
Product Number	815310	815315	815320	815325	815335	815345	815350	815355	815360



Fence Building Attachments

Standard Duty Hydraulic Post Drivers (Wood / Steel Post) Complete Drivers (including mounts) for Tractors or Skid Steers. Skid Steer units are designed with "Universal" style quick attach, return line fitting kit is required, unless noted. Note: All post drivers include a Post Holder as standard equipment.					
Product	Model	Item #	Description	Lbs.	List
	HPD-16	814400	Center Mount for Tractor 3-pt (Cat I/II). Manual Adjustment driver w/ stabilizer legs. Maximum post size 5" x 9'	600	5,215.00
	HPD-16HSS	814630	Skid Steer Mounted all Hydraulic Adjustment driver. Maximum post size 5" x 9'	950	10,563.00
	HPD-16HSS/P	815020	Skid Steer Mounted self-contained all Hydraulic Adjustment driver. No special return line fittings are required. Maximum post size 5" x 9'	1283	15,771.00
	HPD-16SHC	814825	Center Mount for Tractor 3-pt (Cat. I/II). All Hydraulic Adjustment driver. Maximum post size 5" x 9'	875	9,016.00

Fence Building Attachments

Hydraulic Post Drivers with Q-Technology (Wood / Steel Post) Complete Drivers (including mounts) for Tractors or Skid Steers. Units feature Q-Technology – “Quick Change”- Rod Seal & “Quick Change”- Springs. Skid Steer units are designed with “Universal” style quick attach, return line fitting kit is required, unless noted. Note: All post drivers included a Post Holder as standard equipment.					
	HPD-22Q	815300	Center Mount for Tractor 3-pt (Cat I/II). Manual Adjustment driver w/ stabilizer legs. Maximum post size 8-3/4” x 10’	795	7,245.00
	HPD-22Q HSS	815320	Skid Steer Mounted all Hydraulic Adjustment driver. Maximum post size 8-3/4” x 10’	1245	12,593.00
	HPD-22Q HSS/P	815325	Skid Steer Mounted self-contained all Hydraulic Adjustment driver. No special return line fittings are required. Maximum post size 8-3/4” x 10’	1385	17,801.00
	HPD-22Q SHC	815330	Center Mount for Tractor 3-pt (Cat. I/II). All Hydraulic Adjustment driver. Maximum post size 8-3/4” x 10’	1035	11,046.00
Product	Model	Item #	Description	Lbs.	List
	HPD-26Q SHC	815345	Center Mount for Tractor 3-pt (Cat. II). All Hydraulic Adjustment driver. Maximum post size 11” x 10’	1215	13,223.00
	HPD-26Q HSS	815350	Skid Steer Mounted all Hydraulic Adjustment driver. Maximum post size 11” x 10’	1429	14,770.00
	HPD-26Q HSS/P	815355	Skid Steer Mounted self-contained all Hydraulic Adjustment driver. No special return line fittings are required. Maximum post size 11” x 10’	1575	19,978.00
Note: MSS & HSS models for skid steer loaders require the purchase of a return line package for proper operation,					

Fence Building Attachments

Post Driver Accessories and Mounts. Mounting Kits are listed to allow conversion of standard Post Driver.					
	Post Holder	815130	Fits Worksaver hydraulic post drivers previously manufactured without post holders. Spring loaded, holds post in position until post is started. Not for "T" posts. Can ship UPS.	25	294.00
	T-Post Holder	814490	Adapter for holding Steel "T" Post	11	126.00
Manual Mount Kits For 3-pt Only		815250	Manual Adjustment Base with 3-pt mount and stabilizer legs	168	1,687.00
Skid Steer Mounts		814610	Hydraulic Adjustment (HSS) mount for Skid Steer. Models 16, 22Q & 26Q drivers	514	7,035.00
		815000	Optional Hydraulic Power Package for hydraulic adjustment Skid Steer mounts. Contains, hydraulic motor w/self-contained hydraulic system. (Use with mount 814610)	201	5,208.00
Hydraulic Mount Kits For 3-pt Only		814680	Hydraulic adj. center mount (SHC) only for HPD-16, 22Q, & 26Q drivers.	380	5,488.00

Note: MSS & HSS models for skid steer loaders require the purchase of a return line package for proper operation,

Fence Building Attachments

Return Line Kits for Skid Steer Mounted Post Drivers Return Line kits are required for all MSS & HSS (except HSS/P) models. These kits contain fittings to allow the oil to be returned to the hydraulic reservoir.					
Product	Model	Item #	Description	Lbs.	List
	Bobcat	814905	Return line fittings, hoses, and hardware for S200, S250, S300, S330, T250, T300, T320, T630, T650 and earlier models except 773G & 873G (Note: approx. 4" dia. screw type plastic cap)	5	217.00
	Bobcat	814908	For Models S130, S150, S160, S175, S185, T140, T190 (Rubber plug type cap)	6	217.00
	Case	815105	For most 1835, 1835B, 1835C, 1840, 1845, 1845B & 1845C (Large Diameter Cap)	7	357.00
	Case	814915	For Models 410, 420, 430, 435, 440, 445, 450, 465 40XT, 60XT, 70XT, 75XT, 85XT, 90XT, 95XT, SR150, TR270, TR320, SV175, SV185, SV250, SV300, TV380	6	357.00
	Thomas	814915	For All Models including 85, 105, 137, 153, 175, 205, 250, 255	6	357.00
	Daewoo	814915	For All Models including 430, 440, 450, 460, 1340XL	6	357.00
	John Deere	814910	For Units prior to 1/99 Models 375, 575, 3375, 4475, 5575	6	357.00
	John Deere 200-Series	814920	For early 200-series return line fittings, hose and hardware.	6	308.00
	John Deere	815075	For late models 240, 250, 260, 270, 280 with screw type hydraulic reservoir cap	6	217.00
	John Deere	815075	For Models 317, 320, 325, 328, 332 (Side panel must be removed)	6	217.00

Listing Continues on Next Page.

Note: Every attempt has been made to provide return line packages for current skid steer loader models. However, some models are not adaptable, hydraulic fill point is next to loader arm (i.e.: Caterpillar Models, ASV Posi-Track and others). They can be fit with a hydraulic post driver by using a HSS/P model, which is a self-contained units and requires no return line fitting. If you have questions, please consult the factory.

Fence Building Attachments

Return Line Kits for Skid Steer Mounted Post Drivers Return Line kits are required for all MSS & HSS (except HSS/P) models. These kits contain fittings to allow the oil to be returned to the hydraulic reservoir.					
	John Deere	815110	For Models 313, 315, 318D, 319D, 320D, 323D, 326D, 328D, 329D, 332D, 333D, CT315	6	308.00
	Kubota	815115	For Models SVL-75, SVL-90	6	217.00
	Gehl	814895	For All Models including SL3635 SX, SL3935, SL4640, SL4840, SL5640, SL6640, SL7810, V270, V330, V400, 6640, 5240, 3640E, 4240E, 5240E, 5640E, 6640E, RT175, RT210, CTL85	7	217.00
	Mustang	814940	For Models including 2022, 2032, 2040, 2050, 2060, 2070, 2044, 2054, 2066, 2099,	6	231.00
	Mustang	814895	For Models including 2026, 2041, 2076, 2086, 2109, 2700V, 3300V, 1750RT, 2100RT, MTL 325	6	217.00
	New Holland	814910	For All Models including LS120, LS125, LS140, LS150, LS160, LS170, LS175, LS180, LS185.B, LS190.B, C175, C185, C190, L553, L554, L555, L781, L783, L784, LX665, LX865, LX885, LX985	6	357.00
	New Holland Prior to 2015	815055	For 200 series Models L213, L215, L218, L220, L223, L225, L230, C227, C232, C238	6	357.00

Note: Every attempt has been made to provide return line packages for current skid steer loader models. However, some models are not adaptable (i.e.: Caterpillar Models, ASV Posi-Track and others). They can be fit with a hydraulic post driver by using a HSS/P model, which is a self-contained units and requires no return line fitting. If you have questions, please consult the factory.