

Our Post Hole Diggers Dig Deeper, Faster & Smarter

Engineered to allow the operator to dig deeper, faster and smarter, Worksaver's complete line of PTO powered diggers offer time saving convenience with outstanding reliability. Shear-bolt protected driveline is coupled to a rugged gearbox featuring tapered roller bearings and spring-loaded seals for extended service life. Large 2" output shaft has two-bolt auger connection for reliable power transfer. All job matched augers utilize fishtail center points with double flighting on the first turn for quick, positive digging action right from the start.



300 PHD shown
with optional
Parking Stand Kit



See it in action!

Model 300

Digger for Sub-compact Tractors

Ideal for the small acreage owners, Model 300 mates to most sub-compact tractors with a Cat. 0 or limited Cat. I three point hitches. Standard positioning handle allows the operator to place the digger from the tractor seat. Augers 30" in length are offered in 6", 9" and 12" diameters providing versatility when digging holes.

Model 500

Standard Duty Digger

Our most popular digger, the Model 500 standard duty, offers 3-position boom adjustment allowing it to adapt to most tractors. Tubular steel stock of 2.875" diameter is used for the boom for increased durability. Horseshoe yoke allows the unit to operate on Cat I/II tractors offering the operator versatility of use. Job matching augers is easy; they are 42" in length in 6", 9" and 12" diameters in single and double flight configuration. Positioning handle is standard equipment.



500 PHD

Worksaver



Model 720 Heavy-duty Digger

Increased performance is offered in the Model 720 heavy-duty digger. Designed for Cat. I/II tractors, this model offers 3-position boom adjustment, rugged gearbox along with 3-1/2" diameter boom for dependable operation. Augers (42" length) are available in 6", 9", 12", 14", 18" and 24" diameters in single and double flight plus standard or heavy-duty configuration offering the outmost in productivity.



720 PHD



925 PHD

Model 925 Industrial Duty Digger

Industrial duty workhorse, Model 925, provides dependable operation when mated with any auger from 6" to 30" in diameter. It fits any Cat I/II tractor with 540 rpm PTO. When maximum performance is required, the 4.1:1 ratio gearbox provides the torque to make the operator more productive.



Augers — Fishtail center point and high carbon, alloy steel digger teeth offer dependable operation with long component life. Augers range in diameter from 6" to 30" single or double flight, standard duty or heavy duty with reinforced collars and heavier flighting allows the operator to choose the auger that is right for the job.



Optional Down Force Kits — Provide 350-500 lbs. of extra pressure, increasing performance in tough digging conditions. Available for models 500, 720 and 925 post hole diggers. (not for small, compact tractors)

Models 614/624HC, 714/724HC, 914HC/924HC & 924HC-Euro Hydraulic Post Hole Diggers

Worksaver offers a complete line of hydraulically driven post hole diggers with models for 3-pt, skid steers and tractor loaders. Offering includes the 614HC/624HC 3-pt mounted models, 714HC/724HC bolt-on units, 814HC/824HC clamp-on, 914HC/924HC skid steer mount units and the 924HC/Euro mount for tractor loaders. Power is provided by a field proven hydraulic drive motor and gearbox combination for a smooth transfer of power to the auger.



924HC PHD

Models 914HC, 924HC Skid Steer Mounted Hydraulic Post Hole Digger

Increase your reach over shrubs, fence lines and other obstructions with a skid steer mounted 914HC/924HC hydraulically driven digger. It's a great time saver with exceptional up-front visibility and control. Frame design incorporates a gearbox cradle to eliminate auger swing during transport. Choose from 6" to 24" diameter augers. Counter weights assures the digger maintains its vertical position. Note: These diggers will also fit on tractor loaders equipped with the "universal" skid steer attaching system. Models are also available for tractor loaders with the Euro/Global bucket quick attach system.



714HC PHD

Models 714HC, 724HC Bolt-on Hydraulic Post Hole Digger

Increase productivity with these bolt-on hydraulic diggers. Mounts to side of any loader bucket allowing the operator an unobstructed view of the task at hand. Counter weights assure the digger maintains its vertical position while the loader provides the down force for reliable digging.



WARNING: Do not work, climb or stand near operating diggers. Retrofit safety guards are available for all older Worksaver diggers and extensions. Please state model of digger when ordering.




Post Hole Diggers Specifications

STD - Standard Duty Augers for use in lighter soils, free of stones, roots etc.





HDSF- Heavy Duty Single Flight Augers for use when encountering tougher digging conditions or where stones, roots, etc. may be present.

HDDF - Heavy Duty Double Flight Augers for use when operating in loose flowable soils such as sand/gravel, designed to help carry soil to the surface of the hole.

| Model | 300 | 500 | 720 | 925 | 614HC | 624HC |
|-------------------------|---------------------------|---------------------------|---------------------------|---------------------------|---------------------------|---------------------------|
| Boom Size (O.D.) | 2.875" | 2.875" | 3-1/2" | 3-1/2" | 3-1/2" | 3-1/2" |
| Yoke Size | 1/2" x 3" HRF | 3" | 3" | 3" | 3" | 3" |
| Boom Positions | 3 | 3 | 3 | 3 | 3 | 3 |
| Mount Type | Cat. 0 (7/8" pins) | Cat. I/II | Cat. I/II | Cat. I/II | Cat. I/II | Cat. I/II |
| Gearbox Ratio | 3:1 | 3:1 | 3.18:1 | 4.1:1 | 3.18:1 | 3.18:1 |
| Gearbox Output Shaft | 2" | 2" | 2" | 2" | 2" | 2" |
| Gearbox Bearings | Tapered Roller | Tapered Roller | Tapered Roller | Tapered Roller | Tapered Roller | Tapered Roller |
| Gearbox Seals | Double lip, spring loader | Double lip, spring loader | Double lip, spring loader | Double lip, spring loader | Double lip, spring loader | Double lip, spring loader |
| Drive Type | PTO, 540 RPM | PTO, 540 RPM | PTO, 540 RPM | PTO, 540 RPM | Hydraulic | Hydraulic |
| Shear Bolt | Yes, Grade 2 | Yes, Grade 2 | Yes, Grade 2 | Yes, Grade 2 | N/A | N/A |
| Gearbox Ltd. Warranty | 5-yrs. | 5-yrs. | 5-yrs. | 5-yrs. | 5-yrs. | 5-yrs. |
| Tractor hp | up to 25 hp | 20 - 35 hp | 25-65 hp | 35 - 95 hp | N/A | N/A |
| Hyd. Requirement | N/A | N/A | N/A | N/A | 5-10 GPM | 10-20 GPM |
| Hyd. Pressure psi | N/A | N/A | N/A | N/A | 1500-3000 | 1500-3000 |
| Optional Down Force Kit | N/A | Yes, DFK-50 | Yes, DFK-70 | Yes, DFK-90 | Yes, DFK-70 | Yes, DFK-70 |
| Auger Sizes | 6" thru 12" | 6" thru 12" | 6" thru 24" | 6" thru 30" | 6" thru 14" | 6" thru 24" |
| Auger Length | 30" | 42" | 42" | 42" | 42" | 42" |
| Auger Type | STD | STD, HDSF, HDDF | STD, HDSF, HDDF | STD, HDSF, HDDF | STD, HDSF, HDDF | STD, HDSF, HDDF |
| Auger Point - Bolt-in | Fish Tail | Fish Tail | Fish Tail | Fish Tail | Fish Tail | Fish Tail |
| 12" Auger Ext. | N/A | Opt. (170705) | Opt. (170705) | Opt. (170705) | Opt. (170705) | Opt. (170705) |
| Parking Stand Kit | Opt. (102160) | Opt. (102165) | Opt. (102165) | Opt. (102170) | Opt. (102165) | Opt. (102165) |
| Weight (lbs.) | 149 | 160 | 206 | 210 | 180 | 182 |
| Product Number | 170545 | 170990 | 706160 | 709540 | 702090 | 702095 |


| Model | 714HC | 724HC | 914HC | 924HC | 924HC/Euro |
|-----------------------|---------------------------|---------------------------|---------------------------|---------------------------|---------------------------|
| Mount Type | Bolt-on | Bolt-on | Skid Steer | Skid Steer | Euro/Global |
| Gearbox Ratio | 3.18:1 | 3.18:1 | 3.18:1 | 3.18:1 | 3.18:1 |
| Gearbox Output Shaft | 2" | 2" | 2" | 2" | 2" |
| Gearbox Bearings | Tapered Roller | Tapered Roller | Tapered Roller | Tapered Roller | Tapered Roller |
| Gearbox Seals | Double lip, spring loaded | Double lip, spring loaded | Double lip, spring loaded | Double lip, spring loaded | Double lip, spring loaded |
| Drive Type | Hydraulic | Hydraulic | Hydraulic | Hydraulic | Hydraulic |
| Shear Bolt | N/A | N/A | N/A | N/A | N/A |
| Gearbox Ltd. Warranty | 5-yrs. | 5-yrs. | 5-yrs. | 5-yrs. | 5-yrs. |
| Hyd. Requirement | 5-10 GPM | 10-20 GPM | 5-10 GPM | 10-20 GPM | 10-20 GPM |
| Hyd. Pressure psi | 1500-3000 | 1500-3000 | 1500-3000 | 1500-3000 | 1500-3000 |
| Auger Sizes | 6" thru 14" | 6" thru 24" | 6" thru 14" | 6" thru 24" | 6" thru 24" |
| Auger Length | 42" | 42" | 42" | 42" | 42" |
| Auger Type | STD, HDSF, HDDF | STD, HDSF, HDDF | STD, HDSF, HDDF | STD, HDSF, HDDF | STD, HDSF, HDDF |
| Auger Point - Bolt-in | Fish Tail | Fish Tail | Fish Tail | Fish Tail | Fish Tail |
| 12" Auger Ext. | Opt. (170705) | Opt. (170705) | Opt. (170705) | Opt. (170705) | Opt. (170705) |
| Weight (lbs.) | 125 | 127 | 208 | 210 | 220 |
| Product Number | 702100 | 702105 | 702120 | 702125 | 702135 |

Fence Building Attachments


| Post Hole Diggers, PTO & Hydraulic Driven Post Hole Diggers for Tractors or Skid Steers.. Prices shown are less auger. | | | | | |
|--|-------|--------|--|------|----------|
| Product | Model | Item # | Description | Lbs. | List |
| | 300 | 170545 | Low-profile model, 3-pt mounted. PTO driven with shear-bolt protection. For sub-compact tractors (14-24 hp). Cat. O with 7/8" pins. Requires use of 30" long augers. Ships in one carton. (Uses 6"-12" augers) | 149 | 1,253.00 |
|  | 500 | 170990 | Standard-duty model, 3-pt mounted. PTO driven. Shear-bolt protected. (6"-12" augers) Cat. I/II with 7/8" pins. Ships in one carton. | 160 | 1,281.00 |
|  | 720 | 706160 | Heavy-duty 3-pt mounted. PTO driven. Shear-bolt protected. (6" –24" augers) Cat. I/II with 7/8" pins. Ships in one carton. | 206 | 1,631.00 |
| | 925 | 709540 | Industrial-duty 3-pt mounted. PTO driven. Shear-bolt protected. (6" – 30" augers) Cat. I/II with 7/8" pins. Ships in one carton. | 210 | 2,051.00 |
|  | 614HC | 702090 | 3-pt mounted Post Hole Digger. Hydraulically driven. Requires 5 – 10 gpm Hydraulic Flow @1500-3000 psi. (6"-14" augers) Includes hoses less ends. | 180 | 2,989.00 |
| | 624HC | 702095 | 3-pt mounted Post Hole Digger. Hydraulically driven. Requires 10 – 20 gpm hydraulic flow. @1500-3000 psi. (6"-24" augers) Includes hoses less ends. | 182 | 3,045.00 |
|  | 714HC | 702100 | Hydraulic, Bolts on side of loader bucket. Requires 5 – 10 gpm hydraulic flow @1500-3000 psi. (6"-14" augers) Less hoses. | 125 | 2,765.00 |
| | 724HC | 702105 | Hydraulic, Bolts on side of loader bucket. Requires 10 – 20 gpm hydraulic flow @1500-3000 psi. Less hoses. (Uses 6"-24") | 127 | 2,786.00 |

Fence Building Attachments

| Post Hole Diggers, PTO & Hydraulic Driven | | | | | |
|--|------------|--------|--|------|----------|
| Post Hole Diggers for Tractors or Skid Steers.. Prices shown are less auger. | | | | | |
| Product | Model | Item # | Description | Lbs. | List |
| | 924HC | 702125 | “Universal” Skid Steer Mount. Hydraulically Driven. Requires 10-20 gpm @1500-3000 psi. (6”-24” augers) Less Hoses | 210 | 2,877.00 |
| | 914HC | 702120 | “Universal” Skid Steer Mount. Hydraulically driven. Requires 5-10 gpm @ 1500-3000 psi. For tractor front loaders with “Universal” skid steer mount. (less hoses) | 208 | 2,835.00 |
| | 924HC/Euro | 702135 | Euro / Global Mount. Hydraulically Driven. Requires 10 – 20 gpm @ 1500-3000 psi (6”-24” augers) Less Hoses. | 220 | 2,793.00 |

| Post Hole Diggers Accessories | | | | | |
|--|--------|--------|--|------|--------|
| Product | Model | Item # | Description | Lbs. | List |
| Optional Down Force Kits for Increased Digging Pressure. Provides 350-500 lbs. of extra down pressure when digging conditions get tough. Not design for compact or sub-compact tractors under 40 hp. | | | | | |
|  | DFK-50 | 170810 | Down Force Kit for Model 500 PHD. Includes Hydraulic cylinder & hoses | 39 | 637.00 |
| | DFK-70 | 706080 | Down For Kit For Models 720, 614HC & 624HC. Includes Hydraulic cylinder & hoses | 40 | 637.00 |
| | DFK-90 | 709025 | Down Force Kit for Model 925 PHD. Includes Hydraulic cylinders & hoses | 42 | 637.00 |
| Parking Stand Kits for Post Hole Diggers | | | | | |
| | | 102160 | Parking Stand Kit for Model 300 PHD | 11 | 154.00 |
| | | 102165 | Parking Stand Kit for Models 500/720/614H/624H PHD | 12 | 171.00 |
| | | 102170 | Parking Stand Kit for Model 925 PHD | 13 | 185.00 |
| Input / Output Replacement Guard Kits for Older Worksaver Post Hole Diggers Only | | | | | |
| INSTALL SAFETY SHIELDS ON ANY AND ALL OLDER POST HOLE DIGGERS Kits include mounting hardware and safety signs. | | 170520 | For Model 500 Post Hole Digger with Curtis Gearbox. (Note: Gearbox has cast hole for handle on side) | 9 | 53.00 |
| | | 170525 | For Model 500 Post Hole Digger with Comer Gearbox (Note: No threaded holes in bottom of gearbox) | 8 | 53.00 |
| | | 170530 | For Model 500 Post Hole Digger with Comer Gearbox (Note: Threaded holes in bottom of gearbox) | 7 | 53.00 |
| | | 170535 | For Model 706 Post Hole Digger with Omni Gearbox | 9 | 53.00 |
| | | 170540 | Guard for 12” Auger Extension manufactured prior to 1/96 (Note: need to drill hole) | 4 | 53.00 |

Fence Building Attachments

| Augers for Standard to Moderate Digging Conditions All Augers are for 2" O.D. round output shafts only. Retained by two ½" bolt 90 degrees apart. All Augers feature a Bolt-in Fishtail Center Point. | | | | | |
|--|-----------|--------|---|------|----------|
| Product | Model | Item # | Description | Lbs. | List |
| 30 Inch Long Augers for use with Model 300 Post Hole Digger Only | | | | | |
| | 6" SF | 170575 | 6" Single Flight Augers with Teeth | 19 | 273.00 |
| | 9" SF | 170565 | 9" Single Flight Augers with Teeth | 25 | 287.00 |
| | 12" SF | 170570 | 12" Single Flight Augers with Teeth | 28 | 294.00 |
| 42 Inch Long Augers for All Models except Model 300 | | | | | |
|  | 6" SF | 170585 | 6" Std. Duty Single Flight Auger with teeth | 20 | 280.00 |
| | 9" SF | 170710 | 9" Std. Duty Single Flight Auger with teeth | 28 | 287.00 |
| | 12" SF | 170720 | 12" Std. Duty Single Flight Auger with teeth | 32 | 294.00 |
| | 6" HDSF | 706150 | 6" HD Single Flight Auger with teeth. | 22 | 315.00 |
| | 6" HDDF | 706155 | 6" HD Double Flight Auger with teeth | 32 | 350.00 |
| | 9" HDSF | 706109 | 9" HD Single Flight Auger with teeth. | 37 | 364.00 |
| | 9" HDDF | 706009 | 9" HD Double Flight Auger with teeth. | 47 | 392.00 |
| | 12" HDSF | 706112 | 12" HD Single Flight Auger with teeth. | 46 | 406.00 |
| | 12" HDDF | 706012 | 12" HD Double Flight Auger with teeth. | 54 | 455.00 |
| | 14" HDSF | 706033 | 14" HD Single Flight Auger with teeth. | 62 | 490.00 |
| | 14" HDDF | 706037 | 14" HD Double Flight Auger with teeth. | 76 | 567.00 |
| | 18" HDDF | 706070 | 18" HD Double Flight Auger with teeth. | 98 | 840.00 |
| | 24" HDDF | 706075 | 24" HD Double Flight Auger with teeth. | 128 | 1,085.00 |
| | 30" HDDF | 709045 | 30" HD Double Flight Auger with teeth. | 190 | 1,393.00 |
| Landscape Augers | | | | | |
| | 18" HDDFP | 706018 | 18" HD Double Flight Auger with 9" Pilot with teeth and fish tail center point | 108 | 1,190.00 |
| | 24" HDDFP | 706024 | 24" HD Double Flight Auger with 9" Pilot with teeth and fish tail center point | 138 | 1,442.00 |
| Extension, Replacement Center Point & Teeth | | | | | |
| | | 170705 | 12" Auger Extension with guard | 16 | 252.00 |
| | | 175010 | (2) Red Claw cutting teeth w/bolts fits 9"-30" dia. augers & 6" augers mfg. After 6/2000 | 1.35 | 31.00 |
| | | 175080 | Metric Series II U-joint repair kit fits Model 300, 500 built w/ slide collar on tractor end of PTO mfg. After 7/2001 | .55 | 43.00 |
| | | 170430 | Bolt-in Fish Tail Center Point – replacement for augers listed above, retained by ½" bolt | 4 | 53.00 |
| Note: \$10 packaging charge for Augers shipped UPS (under 70 lbs) Only. Larger Augers ship LTL | | | | | |

STD – Standard Duty Augers for use in lighter soils, free of stones, roots etc.

HDSF – Heavy Duty Single Flight Augers for use when encountering tougher digging conditions or where stones, roots, etc. may be present.

HDDF – Heavy Duty Double Flight Augers for use when operating in loose flow-able soils such as sand/gravel, designed to help carry soil to the surface of the hole.