

# Chisel Plow

## 3-Bar Mounted Models



Model CPP-9 Shown with Optional Gauge Wheel Kit

The 3-Bar Chisel Plow was developed over 50 years ago as an alternative to the moldboard plow. The Chisel Plow loosens the soil, begins to manage compaction layers and leaves a good amount of residue on the soil surface, all in one pass. Erosion is controlled while helping to produce increased yields. A wide variety of shank configurations and points allow the producer to fine tune the Chisel Plow to fit his requirements. Optional extension kits allow the 3-Bar Chisel Plow to grow with any operation.

### STANDARD MACHINE SPECIFICATIONS

Unit Height 4'8"	12" Shank Spacing	4" x 4" x 1/4" Frame Structure
Rigid or Dual Nested Spring Shank Mounts	Shank Working Depth - 12" Maximum	Three-Point Hitch - Cat. II, III Free Link
6D283 Shank - 1" x 2" x 26"	Choose One of Three Shank Styles	Adjustable Spring Pressure 550 lbs. to 825 lbs.
6D913 Shank - 1 1/4" x 2" x 32"		Three-Point Hitch - Cat. II, III, IIIN Quick Coupler Hitch
2J644 Shank - 1 1/4" x 2" x 26"	Shank Trip Height - 5 1/2"	LED Warning Lights & SMV Emblem
	Under Frame Clearance - 27 1/2" or 33 1/2"	Powder Coat Paint

Horsepower Requirements: 10 to 15 HP per Shank

Approximate Set-Up Time: 0.25 Hour per Shank

To Order: Select (1) Item from Box A, (1) Item per Foot from Box B, & (1) Item from Box C OR Box D.

### BOX A: BASIC FRAME PRICING INFORMATION (SELECT 1 ITEM)

Model Number	Description	Working Width	Transport Width	Approximate Weight	Suggested List Price
CPP-7	Basic 7' Frame Section	7'	7'6"	604 lbs.	\$ 4,775.00
CPP-9	Basic 7' Frame Section with 2' Extension Kit	9'	8'7"	636 lbs.	5,126.00
CPP-10	Basic 10' Frame Section	10'	10'6"	723 lbs.	5,331.00
CPP-11	Basic 7' Frame Section with 4' Extension Kit	11'	11'6"	779 lbs.	5,743.00
CPP-12	Basic 10' Frame Section with 2' Extension Kit	12'	11'11"	755 lbs.	5,954.00

### BOX B: SHANK & CLAMP ASSEMBLIES PRICING INFORMATION (SELECT 1 ITEM PER FOOT)

Part Number	Description	Approximate Weight	Suggested List Price
RC-26	6D283 Shank & Rigid Clamp Assembly Less Point	39.0 lbs.	\$ 315.00
SC-261	6D283 Shank & Spring Clamp Assembly Less Point	80.0 lbs.	618.00
RCH-32	6D913 Heavy-Duty Shank & Rigid Clamp Assembly Less Point	51.0 lbs.	337.00
SCH-321	6D913 Heavy-Duty Shank & Spring Clamp Assembly Less Point	92.0 lbs.	686.00
RCH-26	2J644 Heavy-Duty Shank & Rigid Clamp Assembly Less Point	46.0 lbs.	328.00
SCH-261	2J644 Heavy-Duty Shank & Spring Clamp Assembly Less Point	82.0 lbs.	627.00

### BOX C: REGULAR CHISEL POINTS PRICING INFORMATION (SELECT 1 ITEM) [3/8" x 2" x 15" WITH BOLTS, NUTS & LOCKWASHERS]

Part Number	Description	Approximate Weight	Suggested List Price
6D759	Box of 7 Reversible Regular Chisel Points	35.0 lbs.	\$ 273.00
6D760	Box of 9 Reversible Regular Chisel Points	45.0 lbs.	350.00
6D165	Box of 10 Reversible Regular Chisel Points	50.0 lbs.	393.00
6D761	Box of 11 Reversible Regular Chisel Points	55.0 lbs.	431.00
6D166	Box of 12 Reversible Regular Chisel Points	60.0 lbs.	466.00

### BOX D: TWISTED SHOVELS PRICING INFORMATION (SELECT 1 ITEM) [3/8" x 3" x 19 1/2" WITH BOLTS, NUTS & LOCKWASHERS]

Part Number	Description	Approximate Weight	Suggested List Price
6D763	Box of 7 Reversible Twisted Shovels	45.0 lbs.	\$ 295.00
6D764	Box of 9 Reversible Twisted Shovels	58.0 lbs.	379.00
6D173	Box of 10 Reversible Twisted Shovels	67.0 lbs.	424.00
6D765	Box of 11 Reversible Twisted Shovels	70.0 lbs.	465.00
6D174	Box of 12 Reversible Twisted Shovels	77.0 lbs.	506.00



# Chisel Plow

## 2-Bar Mounted Models



Model CPPS21-7 Shown with Standard Equipment

The 2-Bar Chisel Plow has been a staple item in the Brillion line-up for over 45 years and provides the most basic of tillage options. With its 5 and 7 shank sizes, it fits the smaller operations and niche markets around the country. The 2-Bar frame allows for handy maneuvering and easy pulling in the field. The ability of these machines to reach just slightly deeper in the soil profile than the moldboard plow allows producers to manage compaction layers to stimulate a better growing environment for their crops.

### STANDARD MACHINE SPECIFICATIONS

Unit Height 4'0"	12" Shank Spacing	4" x 4" x 3/16" Frame Structure
Rigid or Dual Nested Spring Shank Mounts	Shank Working Depth - 12" Maximum	Three-Point Hitch - Cat. II Free Link
6D283 Shank - 1" x 2" x 26"	Adjustable Spring Pressure 550 lbs. to 825 lbs.	Three-Point Hitch - Cat. II, IIIN Quick Coupler Hitch
Under Frame Clearance - 27 1/2"	Shank Trip Height - 5 1/2"	SMV Emblem
Powder Coat Paint		

Horsepower Requirements: 10 to 15 HP per Shank

Approximate Set-Up Time: 0.25 Hour per Shank

### PRICING INFORMATION

Model Number	Description	Working Width	Transport Width	Approximate Weight	Suggested List Price
CPPR2-5	2-Bar Chisel Plow with 5 Rigid Type Shanks	5'	6'6"	455 lbs.	\$ 3,458.00
CPPS21-5	2-Bar Chisel Plow with 5 Spring Type Shanks	5'	6'6"	590 lbs.	4,926.00
CPPR2-7	2-Bar Chisel Plow with 7 Rigid Type Shanks	6'	6'6"	533 lbs.	3,957.00
CPPS21-7	2-Bar Chisel Plow with 7 Spring Type Shanks	6'	6'6"	722 lbs.	6,098.00

### ACCESSORIES & OPTIONAL EQUIPMENT FOR 2-BAR MOUNTED MODELS

Part Number	Description	Approximate Weight	Suggested List Price
9D986	Gauge Wheel Kit (Includes 2 - 7.60L x 15-6 Ply Tires)	176.0 lbs.	\$ 1,918.00
9D991	Box of 5 Reversible Regular Chisel Points with Hardware (5/8" x 2" x 15")	25.0 lbs.	202.00
9D993	Box of 5 Reversible Twisted Shovels with Hardware (3/8" x 3" x 19 1/2")	33.0 lbs.	224.00
6D759	Box of 7 Reversible Regular Chisel Points with Hardware (5/8" x 2" x 15")	35.0 lbs.	273.00
6D763	Box of 7 Reversible Twisted Shovels with Hardware (3/8" x 3" x 19 1/2")	45.0 lbs.	295.00

### ACCESSORIES & OPTIONAL EQUIPMENT FOR 3-BAR MOUNTED MODELS FROM PAGE 9

Part Number	Description	Approximate Weight	Suggested List Price
7D441	Gauge Wheel Kit for Use With 26" Shanks	177.0 lbs.	\$ 1,893.00
6D946	Gauge Wheel Kit for Use With 26" Shanks or 32" Shanks	189.0 lbs.	1,981.00
(Gauge Wheel Kits are always recommended; however, in light soil and row crop work, gauge wheels may not be necessary. One kit per machine - includes 2 - 7.60L x 15-6 Ply Tires.)			
6D226	2' Extension Kit (Converts 7' to 9', 10' to 12')	35.0 lbs.	358.00
6D227	4' Extension Kit (Converts 7' to 11')	198.0 lbs.	1,150.00

