

Bio Shredder

Ø MAX cm 5 / 6 - inch 2









This bio shredder is suitable for semi- professional use. The quality/price ratio is one of the best in its field.

- 1ST QUALITY STEEL FRAME, HIGH STRENGTH, THICKNESS 4 MM LASER CUT, MACHINE BENT AND WELDED BY POROT
- BELT DRIVE WITH TENSIONER
- ROTOR BALANCED ELECTRONICALLY, FORCED VENTILATION, STEEL BEARING SUPPORTS, HIGHLY RESISTANT STEEL SHAFT
- 6 SWINGING REVERSIBLE HAMMERS AND ONE BLADE OF HIGH RESISTANCE TEMPERED STEEL WITH QUICK REPLACEMENT SYSTEM
- ADJUSTABLE COUNTER BLADE, EASILY REPLACEABLE
- SELF-CLEANING SCREEN WITH LONGITUDINAL SLOTS AND QUICK REMOVAL SYSTEM
- TUBELESS TIRES Ø 200 MM WITH STEEL RIMS AND RUBBER TREAD





Туре	A (cm)	B (cm)	C (cm)
Bionda	90	55	105



PACKAGING





Pugio



Ø MAX cm 5 / 6 - inch 2










- 1ST QUALITY STEEL FRAME, HIGHLY RESISTANT, ANTI VIBRATION, THICKNESS 5 MM LASER CUT, MACHINE BENT AND WELDED BY ROBOT
- BELT DRIVE (SECTION B) WITH TENSIONER
- ROTOR: FORCES VENTILATION, STEEL BEARING SUPPORTS, HIGHLY RESISTANT STEEL SHAFT
- 6 SWINGING REVERSIBLE HAMMERS AND ONE BLADE OF HIGH RESISTANCE TEMPERED STEEL WITH QUICK REPLACEMENT SYSTEM, BALANCED ELECTRONICALLY
- ADJUSTABLE COUNTER BLADE, EASILY REPLACEABLE
- SELF-CLEANING SCREEN WITH LONGITUDINAL SLOTS AND QUICK REMOVAL SYSTEM
- TUBELESS TIRES 210 MM DIAMETER WITH STEEL RIMS AND RUBBER TREAD
- PTO VERSION, CATEGORY 1 CARDAN SHAFT - 700 MM
- ENGINE VERSION: IT CAN BE SUPPLIED WITH HONDA GP160 OR GP200 ENGINE







Model OPTIONAL Pricing

3 point hitch for tractor PTO 846.00

DIMENSIONS Type A (cm) B (cm) C (cm) Pugio 90 72 105









Bio Shredder

Ø MAX cm 5 - 6 - inch 2




Bio shredder designed for semi-professional use. It guarantees reliable and efficient operation.




- 1ST QUALITY STEEL FRAME, HIG RESISTANT, ANTI VIBRATION, THICKNESS 5 MM LASER CUT, MACHINE BENT AND WELDED BY ROBOT
- BELT DRIVE (SECTION B) WITH TENSIONER
- ROTOR: FORCES VENTILATION, STEEL BEARING SUPPORTS, HIGHLY RESISTANT STEEL SHAFT
- 6 SWINGING REVERSIBLE HAMMERS AND TWO BLADES OF HIGH RESISTANCE TEMPERED STEEL WITH QUICK REPLACEMENT SYSTEM, BALANCED ELECTRONICALLY
- ADJUSTABLE COUNTER BLADE, EASILY REPLACEABLE
- SELF-CLEANING SCREEN WITH LONGITUDINAL SLOTS AND QUICK REMOVAL SYSTEM
- TUBELESS TIRES 210 MM DIAMETER WITH STEEL RIMS AND RUBBER TREAD
- PTO VERSION, CATEGORY 1 CARDAN SHAFT - 700 MM
- ENGINE VERSION: IT CAN BE SUPPLIED WITH HONDA GP200 OR GX270 ENGINE








Туре	A (cm)	B (cm)	C (cm)
Vulcan	90	55	105









Bio Shredder

Ø MAX cm 7 - 9 - inch 3







This bio shredder is both reliable and safe. It surpassed all the tests to assure the safety of the operator and assure the shredding performance with top marks.

- 1ST QUALITY STEEL FRAME, HIGH STRENGHT, ANTI VIBRATION, THICKNESS 5 MM LASER CUT, MACHINE BENT AND WELDED BY ROBOT
- "V" BELT TRANSMISSION SECTION B WITH TENSIONER
- ROTOR: FORCED VENTILATION, STEEL BEARING SUPPORTS, HIGHLY RESISTANT STEEL SHAFT
- 6 SWINGING REVERSIBLE HAMMERS AND 2 BLADES OF HIGHLY RESISTANT TEMPERED STEEL WITH QUICK REPLACEMENT SYSTEM, BALANCED ELECTRONICALLY
- 2 ADJUSTABLE COUNTER BLADES, EASILY REPLACEABLE.
- SELF CLEANING SCREEN WITH LONGITUDINAL SLOTS AND QUICK REMOVAL SYSTEM
- PNEUMATIC TIRES 330 MM DIAMETER
- PTO VERSION WITH CATEGORY 1, UNIVERSAL PTO SHAFT - 700 MM
- ENGINE VERSION: IT CAN BE SUPPLIED WITH HONDA GX270 OR GX390 ENGINE









Scutum



55

120

110





Bio Shredder

Ø MAX cm 10 - inch 4







A professional chipper/ shredder with gravity-feed and high-level discharge. Reliability and safety are key elements of this machine.

- HIGHLY RESISTANT STEEL FRAME, CUT, BENT AND WELDED BY ROBOT
- V BELT TRANSMISSION WITH 2 BELTS (SECTION B) WITH SCREW TENSIONER
- 3 POINT HITCH, CATEGORY 4 PTO SHAFT
- 4 REVERSIBLE CHIPPING BLADES OF HIGH RESISTANCE STEEL MOUNTED ON A VENTILATED DISC.
- QUICK ACCESS TO THE ROTOR FOR EASY BLADES REPLACEMENT.
- CHIPPER DISC HAS STEEL BEARING SUPPORTS AND IS ELECTRONICALLY BALANCED.
- SELF-FEED (GRAVITY) HOPPER, CHIPPING DISC PULLS BRANCHES IN AS IT CHIPS, MAX DIAMETER 110MM (4.5 INCH).
- MATERIAL DISCHARGE 1.5M (5 FOOT) HIGH AND 360° ADJUSTABLE





Туре	A (cm)	B (cm)	C (cm)
Argo	170	120	170









Bio Shredder

Ø MAX cm 12-14 - inch 5









A professional chipper/ shredder with high level discharge. A "No Stress" version is available which automatically adjusts the feed rollers to prevent the engine swintching-off of the tractor. Reliability and safety are key elements of this machine.

- HIGHLY RESISTANT STEEL FRAME, CUT, BENT AND WELDED BY ROBOT
- V BELT TRANSMISSION WITH 2 BELTS (SECTION B) WITH SPRING LOADED TENSIONER
- VENTILATED HOLDER DISC, STEEL BEARING SUPPORTS, ROTOR SHAFT IN HIGH RESISTANCE STEEL, DISC 35 MM THICKNESS AND 500 MM DIAMETER
- QUICK ACCESS TO BLADE HOLDER FOR EASY BLADE REPLACEMENT
- 4 REVERSIBLE BLADES OF HIGH RESISTANCE STEEL
- INDEPENDENT HYDRAULIC SYSTEM. FEED ROLLER WITH INVERSION DEVICE AND SECURITY VALVE
- 3 POINT HITCH, CATEGORY 4 PTO SHAFT - 700 MM
- DISCHARGE 2 M HIGH AND ADJUSTABLE 360°. MAX WOOD CUT DIAMETER 140 MM (5 INCH.)





Туре	A (cm)	B (cm)	C (cm)
Scorpion	180	130	145
Scorpion NS	180	130	145



PACKAGING

Pallet \$73.00



