

DM 50

DEL MORINO – Potato Digger

Potato digger

HP

12 - 30

kW

10 - 22

rpm

540







cm 15 - 30 - inch 6 - 12




STANDARD FEATURES

- 3 POINT HITCH, CATEGORY 1. DRIVE SHAFT AT 540 RPM
- 1 FIXED PLOWSHARE. OSCILLATING SIEVE SEPARATES POTATOES FROM SOIL
- ADJUSTABLE WHEELS FOR DEPTH CONTROL
- UNIVERSAL PTO SHAFT CATEGORY 1
- REAR DISCHARGE

Model	hp							Pricing
		cm	in	cm	in	kg	lbs	
DM 50	12 - 30	50	20"	90	36"	155	342	3,615.00

DIMENSIONS

Type	A (cm)	B (cm)	C (cm)
DM 50	140	90	100




DEL MORINO – Potato Digger**DM 100****Potato digger****HP****30 - 50****kW****22 - 40****rpm****540****cm 15 - 30 - inch 6 - 12****STANDARD FEATURES**

- THREE-POINT HITCH, CATEGORY 1. DRIVE SHAFT WITH FLYWHEEL, 540 RPM
- STEEL FLYWHEEL THREE INTERCHANGEABLE FURROWS
- OSCILLATING SIEVES SEPARATE POTATOES FROM SOIL
- ADJUSTABLE STEEL DISCS FOR DEPTH CONTROL
- UNIVERSAL PTO SHAFT CATEGORY 4
- SIDE DISCHARGE

Model	hp							Pricing
		cm	in	cm	in	kg	lbs	
DM 100	30 - 50	60	24"	150	60"	305	762	4,701.00

DIMENSIONS

Type	A (cm)	B (cm)	C (cm)
DM 100	160	170	105



BPO A

DEL MORINO – Potato Digger

Potato digger with connecting bar

HP

12 - 30




kW

10 - 22



**STANDARD
FEATURES**

- COMPLETELY WELDED STEEL FRAME
- ELEMENTS: LASER CUT AND AUTOMATIC BENDING MACHINES WITH CNC CONTROL
- 2 OR 3 ELEMENTS WITH RELATED FLANGES; HIGHLY RESISTANT TEMPERED STEEL
- CATEGORY 1
- INTERCHANGEABLE ELEMENTS
- FLANGES TO ADJUST THE DISTANCE BETWEEN ELEMENTS
- ELECTROSTATIC COATING

						
Model		cm	in	kg	lbs	Pricing
BPO A 2	Bar with 2 elements	150	60	80	176	884.00
BPO A 3	Bar with 3 elements	150	60	100	220	1,075.00