

# DEL MORINO – Mowers

## ET 100

Finishing mower

HP

12 - 25

kW

10 - 20

rpm

540



cm 2-9 - inch 1-4



Three different operation modes in one finishing mower: mulching, side discharge and rear discharge. It is perfect for low HP tractors.



### STANDARD FEATURES


- 3 POINT HITCH, CATEGORY 1
- ALUMINUM GEARBOX 540 RPM WITH INTEGRATED FREE WHEEL DEVICE
- DIRECT DRIVE
- 1 ROTOR WITH 1 BLADE
- ADJUSTABLE HEIGHT
- PIVOTING WHEELS
- UNIVERSAL PTO SHAFT CATEGORY 2 - 1000 MM

Model	hp	cm	in	cm	in	n.	kg	lbs	Pricing
<b>ET 100</b>	<b>12 - 25</b>	<b>100</b>	<b>40"</b>	<b>110</b>	<b>44"</b>	<b>1</b>	<b>125</b>	<b>276</b>	<b>1,793.00</b>



**DIMENSIONS**

Type	A (cm)	B (cm)	C (cm)
ET 100	<b>120</b>	<b>110</b>	<b>60</b>



**PACKAGING**

Single metal crate

\$75.00



# SRM

Rear finishing mower side discharge

HP  
12 - 70

kW

10 - 50

rpm

540 / 1000 / 2000

cm 2-9 - inch 1-4








This side discharge finishing mower has a high quality cutting system for professional quality and efficient cutting of large areas.




## STANDARD FEATURES


- 3 POINT HITCH, CATEGORY 1
- CAST IRON GEARBOX 540 RPM
- BELT DRIVE
- THREE SPINDLES EACH WITH SINGLE BLADE
- SIDE DISCHARGE
- OPTIONAL MULCH-SYSTEM
- ADJUSTABLE HEIGHT, PIVOTING WHEELS
- UNIVERSAL PTO SHAFT, CATEGORY 2 - 1000 MM
- CENTRAL LUBRICATION


Model	hp					n.			Pricing
		cm	in	cm	in				
<b>SRM 120</b>	<b>12 - 70</b>	<b>120</b>	<b>48"</b>	<b>145</b>	<b>58"</b>	<b>3</b>	<b>177</b>	<b>390</b>	<b>2,345.00</b>
<b>SRM 150</b>	<b>12 - 70</b>	<b>150</b>	<b>60"</b>	<b>180</b>	<b>72"</b>	<b>3</b>	<b>207</b>	<b>456</b>	<b>2,580.00</b>
<b>SRM 180</b>	<b>12 - 70</b>	<b>180</b>	<b>72"</b>	<b>215</b>	<b>86"</b>	<b>3</b>	<b>233</b>	<b>514</b>	<b>3,014.00</b>
<b>SRM 215</b>	<b>12 - 70</b>	<b>215</b>	<b>85"</b>	<b>250</b>	<b>100"</b>	<b>3</b>	<b>285</b>	<b>628</b>	<b>3,418.00</b>

Model	OPTIONAL	Type	Pricing	
	<b>KM</b>	Kit mulching - deflectors for frequent cuts	SRM 120	<b>375.00</b>
			SRM 150	<b>445.00</b>
			SRM 180	<b>487.00</b>
			SRM 215	<b>527.00</b>

Model		Pricing
	<b>A</b>	Anti-scalp roller-land with speed bump
		<b>131.00</b>

Model		Type	Pricing	
	<b>R1</b>	Gear box 1000 RPM or 2000 RPM	1.000 rpm	<b>392.00</b>
			2.000 rpm	<b>401.00</b>


Model		Pricing
	<b>P</b>	Pneumatic tires- soft lawn and land
		<b>265.00</b>

Model		Pricing
	<b>G</b>	Hard rubber wheel - no punctures
		<b>401.00</b>

Model		Pricing
	<b>FM</b>	Front mount - Attelage frontal
		<b>337.00</b>

**DIMENSIONS**

Type	A (cm)	B (cm)	C (cm)
SRM 120	<b>130</b>	<b>120</b>	<b>60</b>
SRM 150	<b>160</b>	<b>120</b>	<b>60</b>
SRM 180	<b>190</b>	<b>120</b>	<b>60</b>
SRM 215	<b>220</b>	<b>120</b>	<b>60</b>



**PACKAGING**

Single metal crate \$75.00



## PRM

Rear finishing mower rear discharge

HP  
12 - 70

kW

10 - 50

rpm

540 / 1000 / 2000



cm 2-9 - inch 1-4




This rear discharge finishing mower has a high quality cutting system for professional quality and efficient cutting of large areas.




### STANDARD FEATURES

- 3 POINT HITCH, CATEGORY 1
- CAST IRON GEARBOX 540 RPM
- 2 - BELT DRIVE
- 3 SPINDLES EACH WITH SINGLE BLADE, XRM 235: 5 SPINDLES EACH WITH SINGLE BLADE
- REAR DISCHARGE
- OPTIONAL MULCH-SYSTEM
- ADJUSTABLE HEIGHT, PIVOTING WHEELS
- UNIVERSAL PTO SHAFT, CATEGORY 2 - 1000 MM, XRM - 800 MM
- CENTRAL LUBRICATION

Model	hp	cm	in	cm	in	n.	kg	lbs	Pricing
<b>PRM 120</b>	12 - 70	120	48"	130	52"	3	180	397	2,694.00
<b>PRM 150</b>	12 - 70	150	60"	160	64"	3	211	465	2,943.00
<b>PRM 180</b>	12 - 70	180	72"	190	76"	3	239	527	3,250.00
<b>PRM 215</b>	12 - 70	215	85"	225	90"	3	289	637	3,597.00
<b>XRM 235</b>	12 - 70	235	93"	245	98"	5	320	705	4,291.00

Model	OPTIONAL	Type	Pricing	
	<b>KM</b>	Kit mulching - deflectors for frequent cuts	PRM 120	507.00
			PRM 150	559.00
			PRM 180	620.00
			PRM 215	674.00
			XRM 235	922.00

Model	Pricing
<b>A</b>	134.00

Model	Type	Pricing	
	XRM 235		
<b>R1</b>	Gear box 1000 RPM or 2000 RPM	1.000 rpm	392.00
		<b>R2</b>	2.000 rpm


Model	Pricing
<b>P</b>	265.00

Model	Pricing
<b>G</b>	401.00

Model	Pricing
<b>FM</b>	337.00


**DIMENSIONS**

Type	A (cm)	B (cm)	C (cm)
PRM 120	130	120	60
PRM 150	160	120	60
PRM 180	190	120	60
PRM 215	220	120	60
XRM 235	240	120	60



**PACKAGING**

Single metal crate \$75.00



# DEL MORINO – Mowers

## Omega

3 - Gang mower

HP

40 - 90

kW

30 - 75

rpm


540



cm 2-9 - inch 1-4



This gang mower is an excellent choice for sports fields, parks, large meadows, etc. thanks to its high quality components.




### STANDARD FEATURES


- MAIN FRAME WITH 2 PNEUMATIC TIRES
- TRANSMISSION WITH WIDE ANGLE PTO SHAFT
- MOWERS RAISED AND LOWERED HYDRAULICALLY
- 3 PRM/XRM FINISHING MOWERS WITH CAST IRON GEARBOX 540 RPM AND BELT DRIVE
- REAR DISCHARGE AND OPTIONAL MULCHING SYSTEM
- ADJUSTABLE HEIGHT, PIVOTING WHEELS
- CATEGORY 5, UNIVERSAL SLIP CLUTCH - 1000 MM
- CENTRAL LUBRICATION
- ANTI-SCALP ROLLERS




Model	hp	cm	in	120	150	180	215	235	kg	lbs	Pricing
<b>Omega 11</b>	40 - 90	330	132	3					1244	2743	21,081.00
<b>Omega 12</b>	40 - 90	360	144	2	1				1261	2780	21,231.00
<b>Omega 14</b>	40 - 90	420	168		3				1266	2791	21,404.00
<b>Omega 15</b>	40 - 90	450	180		2	1			1270	2800	21,701.00
<b>Omega 17</b>	40 - 90	510	204			3			1442	3179	22,267.00
<b>Omega 19</b>	40 - 90	565	222			2		1	1479	3261	22,978.00
<b>Omega 21</b>	40 - 90	635	240				2	1	1521	3353	24,756.00

Model	OPTIONAL	Type	Pricing
 <b>KM</b>	Kit mulching - deflectors for frequent cuts	PRM 120	507.00
		PRM 150	559.00
		PRM 180	620.00
		PRM 215	674.00
		XRM 235	925.00
Model			Pricing

<b>O</b>	Wide- angle PTO shaft - closed curves		942.00
----------	---------------------------------------	--	--------

Model			Pricing
 <b>P</b>	Pneumatic tires- soft lawn and land		265.00

Model			Pricing
 <b>G</b>	Hard rubber wheel- no punctures		401.00

**DIMENSIONS**

Type	A (cm)	B (cm)	C (cm)
Omega 11	406	240	240
Omega 12	406	240	240
Omega 14	406	240	240
Omega 15	406	240	240
Omega 17	340	240	240
Omega 19	240	150	240
Omega 21	240	150	240

