


## HD II RAKE





## HD II RAKE FEATURES

### Adjustable Windrow Width

- The windrow width on the HD II can be adjusted hydraulically to a maximum of 72". One hydraulic remote along with the electrical control box, controls all the functions of the rake.
- Because of the offset of the rake wheel beams, there is no need for center kicker wheels.

**5"x7"**  
**Overhead Mainframe**  
• each side opens independently.



**4 SIZES TO  
CHOOSE FROM!  
17, 18, 19 or 20 WHEELS**

### Tractor Mounted Control Box



The rake wheels may be lifted independently left or right or both at the same time with the master switch.

### Torsional Dampening Springs

- Torsional dampening springs allow the rake wheels to roll smoothly over the terrain.



- Rake wheel ground pressure can be adjusted by the threaded rod and nut on the end of the lifting pipes on each rake beam.



- An adjustable hitch and jack are standard equipment.
- Ball hitch is optional.
- The HD II rake features rake beams with a variable adjustment to set the rake wheels straight or in a tilted setting up to 10°. (patented)



- The rake wheel lift pipes slide in oil impregnated bronze bushings and also feature a rake wheel lock for transportation.
- Anti-wrap hay guards are standard equipment.


# HDII Rake Specifications

NUMBER OF WHEELS	17	18	19	20
WHEEL DIAMETER	60"	60"	60"	60"
TEETH PER WHEEL	38	38	38	38
TEETH	RUBBER MOUNTED IN A SET OF 2			
TRANSPORT WIDTH	12'3"	12'3"	12'3"	12'3"
TRANSPORT LENGTH	28'3"	30'9"	30'4"	32'9"
MAXIMUM RAKING WIDTH	30'3"	30'3"	33'3"	33'3"
RAKE WHEEL HUBS	TAPERED BEARINGS	TAPERED BEARINGS	TAPERED BEARINGS	TAPERED BEARINGS
HITCH JACK	STANDARD	STANDARD	STANDARD	STANDARD
TAIL & WORK LIGHTS	STANDARD	STANDARD	STANDARD	STANDARD
TIRES	9.5L X 15SL	9.5L X 15SL	9.5L X 15SL	9.5L X 15SL

## Standard Features



## Effective 9-24



## HD8117 Series *HDII* Rakes

- ❖ **Trailer-Style Hydraulic Open/Close High-Capacity Rake**
- ❖ **Independent Hydraulic Adjust 5"x 7" Backbone Overhead Rear Frame for Windrow Width**
- ❖ **Rear Limited Oscillating Offset Tandem Axle**
- ❖ **61" Rake Wheels w/18 Sets of Rubber Mounted Teeth are Positioned Ahead of Rake Beams**
- ❖ **Rake Wheel Wind Panels**
- ❖ **Independent Rake Wheel Suspension w/Patented**

## BASE UNIT

## Compression Spring System

- ❖ Hydraulic Raise/Lower Independent Rake Wheels
- ❖ Single Point Rake Wheel Down Pressure Adjustment On Each Rake Beam
- ❖ (4) IF240/80R15 Tires/Rims
- ❖ Hydraulic Hoses w/Tips
- ❖ Electric Control Box for All Rake Functions
- ❖ Adjustable Hitch
- ❖ Highway Lighting
- ❖ Jack

Item #	Description	List Price
HD8117	17- Wheel R	\$60,048

## OPTIONS (*NOT Required*)

<b>HDOFNT</b>	2-Wheel Front Extension Kit (1) Rake Wheel added to the Front Rake Beam on each side <i>(Dealer Install)</i>	\$5,723
<b>HDOREAR</b>	Single Wheel Extension Kit (1) Rake Wheel added to the Right Rear Rake Beam – Includes Main Frame Extension Brackets <i>(Dealer Install)</i>	\$3,365
<b>SC10100</b>	10,100# Safety Chain	\$86



Prices and Specifications may be subject to change without notice. Prices do not include shipping or setup.