



TF6128 TWIN-FLEX MERGERS

The ability (with up to 16' windrow cuts) to merge (5) Windrows into one in either direction.....*No additional Cross-Conveyor Extension is needed!*



- ❖ 28' of Continuous Merging with (2) 14' independent Heads.
- ❖ The Self-Contained Hydraulic System features a 35 gallon reservoir coupled with large displacement motors for the Heads and Cross Conveyor, is able to handle "HEAVY" Crops.
- ❖ Patented Center Cam/Center Drive System.
- ❖ Rubber Mounted Teeth.
- ❖ Highest Torque Rated Hydraulic Motors in the Industry, coupled with Heavy 2-Ply Cross-Conveyor Belts.
- ❖ Cross-Conveyor Belts feature a High Torque Drive System....Best in the Industry!
- ❖ Both Models have the ability to merge Left, merge Right, or Split Direction.
- ❖ Requires no Sensors to run the Machine. Very simple to operate.

TF6128 TWIN-FLEX MERGER FEATURES



❖ **Narrowest
Transport Width &
Lowest Height**

❖ **Best-Value
per Linear
Foot of Machine
Width for a (2) Head
Continuous Merger**

The H&S **SOFT SHOE™** Suspension System (patent pending) is a self-contained, self-monitoring hydraulic suspension system for the TF6128 TWIN FLEX™ Merger that provides the softest merger head footprint in the industry, and in all field conditions...wet soils, rough terrain, new seeding, etc.



❖ **Heavy Duty Radial Tires that don't
scuff in the Field (6128)**

TF6128

Working Width	28'2"
Transport Width	8' 6"
Transport Length	25'
Transport Height	9'8"
Pick-up Heads	2 – 14'
Head Travel	20"
Pick-up Strippers	Poly
Pick-up Teeth	Rubber Mounted
Conveyor Belt Width	42"
Cross-Conveyor On/Off Right/Left/Split	In-Cab Electric-over-Hydraulic
Skid Shoe Height	Manual Adjust
Head Suspension	Exclusive "Soft Shoe" Suspension Technology System with In-Cab-Adjust
Drive System	3-Section High Volume Pump
PTO	1000 RPM 1-3/8" or 1-3/4"
Oil Reservoir Capacity	35 Gallon
Tire Size	15R x 19.5
Weight	12,260#
Tractor Size	95 HP Minimum
Hydraulic Requirements	2 Sets of Remotes (Requires Closed Center Hydraulic System) 2750 PSI 12 GPM min.
3-Point Hitch	Cat II, III, or III-N



TF6128 TWIN-FLEX MERGER

BASE UNIT

- ❖ Exclusive “SOFT-SHOE” Suspension Technology
- ❖ 28' 2" Continuous Working Width w/Two Heads
- ❖ Self Contained Hydraulic System
- ❖ 3-Section High Volume Pump
- ❖ 35 Gallon Oil Reservoir
- ❖ 2 Sets of Remotes Needed
- ❖ Patented Center Cam/Center Drive
- ❖ Rubber Mounted Teeth
- ❖ 42" Wide Cross-Conveyor
- ❖ Manual Hydraulic Controls
- ❖ Electric In-Cab Controls for Cross-Conveyor Right/Left/Split/Shut-off
- ❖ Acre Counter
- ❖ Head Height Gauge
- ❖ In-Cab Float Adjustment
- ❖ Manual Adjust Skid Shoes
- ❖ 15R19.5 Radial Tires w/Rims
- ❖ Cat II, III, or III-N 3-Point Hitch
- ❖ Weight - 12,260#

Item #	Description	List Price
TF6128	Twin-Flex 28' Merger SOFT-SHOE™ Suspension	\$159,248

PTO CHOICES (*Required*)

TFO1038PTO	1-3/8" 1000 RPM Standard Length PTO	\$717
TFO1038LPTO	1-3/8" 1000 RPM Long Length PTO	\$717
TFO1034PTO	1-3/4" 1000 RPM Standard Length PTO	\$1,277
TFO1034LPTO	1-3/4" 1000 RPM Long Length PTO	\$1,277

OPTIONS (*NOT Required*)

TFOHSS	Hydraulic Skid Shoe Kit (Dealer Install)	\$6,493
TFODDCC	Dual Drive Cross Conveyor Kit (Dealer Install)	\$3,186

PROIR YEAR OPTIONS (*NOT Required*)

TFORF	Remote Filter Package (Dealer Install)	\$1,355
-------	---	----------------





TF6132 *Twin-Flex* Merger

BASE UNIT

- ❖ Exclusive **SOFT-SHOE™** Suspension Technology
- ❖ 32' of Continuous Working Width w/Two Heads
- ❖ ISOBUS Aux N Compatible
- ❖ Cross Conveyor Right/Left/Split/Shut-off
- ❖ Self-Contained Hydraulic System
- ❖ 65-Gallon Oil Reservoir
- ❖ Patented Center Cam/Center Drive
- ❖ Rubber-Mounted Teeth
- ❖ 42" Wide Cross Conveyor
- ❖ 385/65 x 22.5 Flotation Radial Tires
- ❖ Steering Axle
- ❖ LED Highway Lighting
- ❖ Head Height Gauge
- ❖ Hydraulic Adjust Skid Shoes
- ❖ Cat II, III, or III-N 3-Point Hitch
- ❖ Weight - 17,300#

Item #	Description	List Price
TF6132	<i>Twin-Flex</i> 32' Merger with <i>Soft-Shoe™</i> Suspension	\$244,031

PTO CHOICES (*Required*)

UFO1038PTO	1- $\frac{3}{8}$ " 1000 RPM Standard Length PTO	\$717
UFO1038LPTO	1- $\frac{3}{8}$ " 1000 RPM Long Length PTO	\$717
UFO1034PTO	1- $\frac{3}{4}$ " 1000 RPM Standard Length PTO	\$1,277
UFO1034LPTO	1- $\frac{3}{4}$ " 1000 RPM Long Length PTO	\$1,277

OPTIONS (*NOT Required*)

TFOICC	Control Box for NON-ISOBUS Tractors (<i>Dealer Installed</i>)	\$1,638
HS106742	Keyed Power ISOBUS Adapter fo NON-ISOBUS Tractors (<i>Dealer Installed</i>)	\$750
TFO32GS	12V Grease System (<i>Dealer Installed</i>)	\$5,837

GRASS KITS (*NOT Required*) *Order Through Parts Dept.*

HS104474	28' Grass Kit Option (<i>Dealer Installed</i>)	Contact parts
HS104649	32' Grass Kit Option (<i>Dealer Installed</i>)	dept. for pricing





UF6136 *Twin-Flex* Merger

BASE UNIT

- ❖ Exclusive **SOFT-SHOE™** Suspension Technology
- ❖ 32' of Continuous Working Width w/Two Heads
- ❖ ISOBUS Aux N Compatible
- ❖ Cross Conveyor Right/Left/Split/Shut-off
- ❖ Self-Contained Hydraulic System
- ❖ 65-Gallon Oil Reservoir
- ❖ Patented Center Cam/Center Drive
- ❖ Rubber-Mounted Teeth
- ❖ 42" Wide Cross Conveyor
- ❖ 385/65 x 22.5 Flotation Radial Tires
- ❖ Steering Axle
- ❖ LED Highway Lighting
- ❖ Head Height Gauge
- ❖ Hydraulic Adjust Skid Shoes
- ❖ Weight - 17,300#

Item #	Description	List Price
UF6136	Ultra-Flex 36' Merger with Soft-Shoe™ Suspension	\$275,044

PTO CHOICES (*Required*)

UFO1038PTO	1- ³ / ₈ " 1000 RPM Standard Length PTO	\$832
UFO1038LPTO	1- ³ / ₈ " 1000 RPM Long Length PTO	\$832
UFO1034PTO	1- ³ / ₄ " 1000 RPM Standard Length PTO	\$1,455
UFO1034LPTO	1- ³ / ₄ " 1000 RPM Long Length PTO	\$1,455

OPTIONS (*NOT Required*)

UFOICC	Control Box for NON-ISOBUS Tractors (<i>Dealer Installed</i>)	\$2,731
HS106742	Keyed Power ISOBUS Adapter fo NON-ISOBUS Tractors (<i>Dealer Installed</i>)	\$750
UFO32GS	12V Grease System (<i>Dealer Installed</i>)	\$6,303

GRASS KITS (*NOT Required*) *Order Through Parts Dept.*

HS104406	36' Grass Kit Option (<i>Dealer Installed</i>)	Contact parts dept. for pricing
----------	--	--

