



# DITCHERS

Prices Effective as of



QUALITY BUILT EQUIPMENT

MACHINE

DITCHERS

DRAINAGE & IRRIGATION



## 3 PT & WHEEL DITCHERS

### 3 POINT HITCH DITCHER

Recommended for smaller tractors



- z Includes heavy duty beam with adj-a-screw for tilt.
- z Does not include lift cylinder

6' 3pt. Ditcher approx. 705 lbs \$  .00

7' 3pt. Ditcher approx. 765 lbs \$  .00

#### 3 PT. Ditcher Options

Wing Tilt Cylinder - 3"x 8" Hydraulic Cylinder (a-screw) \$  .00

Estimated set up time: 1/2 hour.  Lift Cylinder - when placed into 3pt beam, \$  .00

### WHEEL DITCHER



Estimated set up time: 2 hours  
z Includes 6:70 x 15" implement tires

z Includes adj-a-screw for tilt

z Requires adj-a-screw or hydraulic cylinder for lift

### 11' WHEEL DITCHER

for canals and large main ditches

- z includes 11L x 15" tires.
- z 4" x 16" tilt cylinder.
- z 5" x 16" lift cylinder & hoses to tractor

Special order only \$  .00

6' Wheel Ditcher approx. 920 lbs \$  .00

7' Wheel Ditcher approx. 980 lbs \$  .00

8' Wheel Ditcher approx. 1090 lbs \$  .00

#### Wheel Ditcher Options

3" x 8" hydraulic cylinder w/ 6' & 7' hoses \$  .00

3" x 8" hydraulic cylinder /w 12' & 13' hoses (in lieu of adj-a-screw) \$  .00

cuts grass, straw or sloughs, helps to eliminate plugging \$  .00



z Lift Cylinder

z Wing Tilt Cylinder

z Coulter Assembly



MACHINE



MACHINE