

# 3PH Rotary Tillers



## FEATURES

- Replaceable Bolt-On Tines
- Self Lubricating Chain Driv
- Adjustable Skidshoes
- Floating Deflecto
- Gear Bo
- 3PH Mount Offse
- Slip Clutc

## SPECIFICATIONS

Models	MKRT486	MKRT546	MKRT606	MKRT726
<b>Horsepower</b>	15-30 HP	20-40 HP	20-50 HP	25-60 HP
<b>Hitch</b>	Cat. 1	Cat. 1	Cat. 1	Cat. 1
<b>Inner Width (in.)</b>	50	54	58	74
<b>Overall Width (in.)</b>	55.375	59.375	63.375	79.375
<b>Weight (lbs.)</b>	491	514	525	636
<b>Number of Flanges</b>	6	6	7	9
<b>Tines/Flange</b>	6 (C-Shape)	6 (C-Shape)	6 (C-Shape)	6 (C-Shape)
<b>Flange Spacing (in.)</b>	7.75	7.75	7.75	7.75
<b>Max Tillage Depth (in.)</b>	6.5	6.5	6.5	6.5
<b>Number of Skid Shoe Settings</b>	5	5	5	5
<b>Rotor Diameter (in.)</b>	17"	17"	17"	17"
<b>Rotor Speed @ 540 PTO (RPM)</b>	211	211	211	211
<b>Gearbox (HP)</b>	50HP @ 540	50HP @ 540	50HP @ 540	50HP @ 540
<b>Drive Chain</b>	#80	#80	#80	#80
<b>List Price</b>	\$5,285.00	\$5,655.00	\$6,215.00	\$6,865.00

# Hydraulic Rotary Tillers



## SPECIFICATIONS

Models	MKRT726HYD-SF	MKRT726HYD-HF
<b>Flow</b>	Standard	High Flow
<b>Hitch</b>	Skidsteer Attachment Plate	Skidsteer Attachment Plate
<b>Inner Width (in.)</b>	74	74
<b>Overall Width (in.)</b>	79.375	79.375
<b>Weight (lbs.)</b>	725	725
<b>Number of Flanges</b>	9	9
<b>Tines/Flange</b>	6 (C-Shape)	6 (C-Shape)
<b>Flange Spacing (in.)</b>	7.75	7.75
<b>Max Tillage Depth (in.)</b>	6.5	6.5
<b>Rotor Diameter (in.)</b>	17"	17"
<b>Drive Chain</b>	#80	#80
<b>List Price</b>	\$6,250.00	\$6,485.00

## FEATURES

- Skid steer attachment plate
- 74" working width
- 9 tine flange
- 6 tines per flang
- Working depth 6.5"
- 17" rotor

Flow Rates	
<b>Standard</b>	16-28 GPM
<b>High Flow</b>	28-40 GPM

*To ensure optimum performance, hydraulic output must match motor package.*