



HARDWARE & ACCESSORIES

PTO Adapters & Accessories

SpeeCo designed and engineered PTO adapters. Yellow zinc dichromate plated.



S16060200



S16060400



S16060700



S16061000



S16064600



S16063000

SKU NUMBER	UPC ITEM NO. 0-87196-	DESCRIPTION	MALE SPLINE	FEMALE SPLINE	EXTENDS PTO	OVERALL LENGTH	MAX H.P.	WEIGHT (lbs.)
S16060000	16600 0	Sleeve increaser; Ford 231082	1-3/8" x 6	1-1/8" x 6	0	2"	75	0.2
S16060200	16602 4	Sleeve increaser; all tractors except Ford	1-3/8" x 6	1-1/8" x 6	0	2-1/4"	75	0.2
S16060300	16603 1	PTO spline adapter; converts 21 spline 1,000 RPM to 6 spline 540 RPM	1-3/8" x 6	1-3/8" x 21	3-1/4"	5-7/8"	75	2.0
S16060400	16604 8	Universal reducer	1-1/8" x 6	1-3/8" x 6	3-5/16" *	5-1/8"	75	1.4
S16060500	16605 5	PTO increaser	1-3/8" x 6	1-1/8" x 6	3-5/8" *	5-1/2"	75	1.3
S16060600	16606 2	PTO short increaser	1-3/8" x 6	1-1/8" x 6	1-1/8" *	3-1/4"	75	0.6
S16060700	16607 9	PTO spline adapter; 20 to 6 spline; set screw lock	1-3/8" x 6	1-3/4" x 20	4-5/8" *	7-1/2"	75	6.1
S16060800	16608 6	PTO extender	1-3/8" x 6	1-3/8" x 6	3-5/16" *	5-1/8"	75	2.2
S16061000	16610 9	PTO spline adapter with quick-release; converts 21 spline 1,000 RPM to 6 spline 540 RPM	1-3/8" x 6	1-3/8" x 21	3-7/8"	6-1/2"	75	2.5
S16061100	16611 6	PTO spline adapter with quick-release; converts 6 spline 540 RPM to 21 spline 1,000 RPM	1-3/8" x 21	1-3/8" x 6	4-1/8" *	6-1/2"	75	2.5
S16061200	16612 3	PTO extender with quick-release	1-3/8" x 6	1-3/8" x 6	4-3/8"	6-1/2"	75	2.8
S16061300	16613 0	PTO extender with quick-release; 21 spline 1,000 RPM	1-3/8" x 21	1-3/8" x 21	4-1/8"	5-7/8"	75	3.2
S16061500	16615 4	PTO spline adapter; 20 to 21 spline; set screw lock	1-3/8" x 21	1-3/4" x 20	4-5/8"	7"	75	4.2
S16061700	16617 8	PTO adapter; heavy duty	1-3/4" x 1-3/8"	1-3/4" x 20	4-5/8"	7-1/2"	75	4.2
S16061800	16618 5	PTO adapter spline; 20 to 21 spline heavy duty	1-3/8" x 21	1-3/4" x 20	4-5/8"	7-1/2"	75	4.3
S16064600	16646 8	Spline adapter; extended length for use with Gresen pump	1-3/8" x 6	1-3/8" x 6	11-5/8"	15"	75	6.0
S16063000	16630 7	Over-running clutch; maximum 1,000 RPM operating speed	1-3/8" x 6	1-3/8" x 6	3-13/16"	6-1/2"	75	5.0
S16063100	16631 4	Over-running clutch; maximum 1,000 RPM operating speed	1-3/8" x 6	1-1/8" x 6	3-13/16"	6-1/2"	75	5.0
S16066000**	16660 4	Over-running clutch with quick-release; maximum 1,000 RPM operating speed	1-3/8" x 6	1-3/8" x 6	4-1/2"	6-3/4"	75	7.2
S16066100**	16661 1	Over-running clutch with quick-release; maximum 1,000 RPM operating speed	1-3/8" x 6	1-1/8" x 6	4-1/2"	6-3/4"	75	7.1

*Approximate length

**Painted yellow

www.speeeco.com • Toll Free: 800-525-8322 • FAX: 303-278-3432