

TREE PULLER

LANDSCAPING



ABOUT THE TREE PULLER

- 28" Single pivoting jaw
- Jaw opens up to 14" wide
- Open plate design increases visibility
- AR400 Serrated teeth provide firm hold
- Greasable jaw pivot pins (1.5")
- Protective Hose Wrap
- Optional - Bolt on Guard Frame
- Optional - Guard Insert (requires frame)

Tree Puller	TRP2814	
Max Jaw Opening (inches)	14	
Jaw Material (inches)	½" AR400	
Max. Cylinder Force	21,000 LBS	
Cylinder Diameter (inches)	3	
Greasable Jaw Pivot Pins (inches)	1.5"	
Overall Width (inches)	51.25"	
Overall Length (inches)	35.25"	
Overall Height (inches)	20.5"	
Machine Weight (lbs)	350	
Max Continuous Operating Pressure	3,000 (PSI)	
Minimum GPM	10	
Base Unit	TRP2814	\$3,150
Base Unit w/ALO Hitch	TRP2814AO600	\$3,150
Base Unit (Blank) (Hoses and couplers not included)	TRP2814BB	\$2,900

Universal Options	Part Numbers	Price
Guard (Push Bar)	TRPGF	\$695
Guard Insert (requires Push bar)	TRPGR	\$325

GUARD (TRPGF)

- An optional bolt on guard frame provides protection for your power unit as well as helps manage the load



GUARD INSERT (TRPGR)

- The guard insert option adds additional protection reducing the amount of poke through from branches

Requires optional Guard



Tree Puller	PART #	Weight	Dimensions
Tree Puller 28"	TRP2814	350 LBS	51 X 35 X 21
Guard (Push Bar)	TRPGF	75 LBS	54 X 30 X 6
Guard Insert (requires push bar)	TRPGR	26 LBS	48 X 21 X 2



**GENERAL
IMPLEMENT**
DISTRIBUTORS