Worksaver

Power Landscape Rakes

Power Landscape Rakes are the ideal tool for the landscape contractor, large property owner, rental yard, park & recreation department or turf management professional. They do it all, prep, smooth, set grade, level, till, remove rocks and create the perfect seedbed.

Carbide Rotor

- Quick-flip side shields are self-storing on the unit allowing ease of windrowing rocks or debris
- Durable triple sealed bearings with bearing protectors for long service life
- Time saving replaceable rotor bearing assemblies
- Choice of rotors – 2" Sabre Tooth or 1-3/4" Carbide Tooth
- Auto adjust chain tensioner is standard on all models

Sabre Rotor

GENERAL IMPLEMENT DISTRIBUTORS

10-Series Powered Landscape Rakes

Elevating productivity, the 10-Series Power Rakes for Mini / Compact Skid Steers features a #80 chain drive, flip-up side shields, dual gauge wheels, adjustable material bar and optional hydraulic angle.

As with all Power Rakes, bearing protectors and environmentally friendly dry chain case are standard equipment.

SPECIFICATIONS –10 Series for Mini Skid Steers w/Universal Mount – * Mounts for Bobcat MT & Gehl available

Model	PXS-410	PXS-510	PXS-610	PXS-410ST	PXS-510ST	PXS-610ST
Mount Type	Mini-SS	Mini-SS	Mini-SS	Mini-SS	Mini-SS	Mini-SS
Main Frame (in)	3 x 3 x 3/16	3 x 3 x 3/16	3 x 3 x 3/16	3 x 3 x 3/16	3 x 3 x 3/16	3 x 3 x 3/16
Overall Width (in/cm)	56/142	68/173	80/203	56/142	68/173	80/203
Working Width (in/cm)	48/122	60/152	72/183	48/122	60/152	72/183
Working Depth (in/cm)	0-3.0/0-8	0-3.0/0-8	0-3.0/0-8	0-3.0/0-8	0-3.0/0-8	0-3.0/0-8
Max. Angle	20° L/R	20° L/R	20° L/R	20° L/R	20° L/R	20° L/R
Hydraulic Angle	Optional	Optional	Optional	Optional	Optional	Optional
Drive System	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic
Rotor Drive	#80 Roller Chain	#80 Roller Chain	#80 Roller Chain	#80 Roller Chain	#80 Roller Chain	#80 Roller Chain
Chain Tensioner	Standard	Standard	Standard	Standard	Standard	Standard
Rotor Tooth	Carbide	Carbide	Carbide	2" Sabre	2" Sabre	Carbide
Gauge Wheel	Dual	Dual	Dual	Dual	Dual	Dual
Flip-up Side Shields	Standard	Standard	Standard	Standard	Standard	Standard
Material Control Bar	Adjustable	Adjustable	Adjustable	Adjustable	Adjustable	Adjustable
Weight (lbs/kg)	524/238	560/254	596/270	526/239	562/255	598/271
Product No.	360600	360605	360610	360615	360620	360625

Choose **Worksaver** For All Your Land Management

GENERAL IMPLEMENT DISTRIBUTORS

Worksaver

20-Series Powered Landscape Rakes

Responsive and reliable, the 20-Series is designed for Skid Steers up to 65 HP. Features a #80 chain drive, dual flip-up gauge wheels, flip-up side shields and an all-welded frame constructed of 3" x 4" x 1/4" tubing.

Also standard are reliable gauge wheels (16 x 6.50-8) mounted to 4-bolt hubs and a "Flex & Float" System offering the operator flexibility to choose maximum down pressure or float position for site prep.

SPECIFICATIONS – 20-Series for Skid Steers under 65 HP

Model	PSS-620	PSS-720	PSS-620ST	PSS-720ST
Mount Type	Skid Steer	Skid Steer	Skid Steer	Skid Steer
Main Frame (in)	3 x 4 x 1/4	3 x 4 x 1/4	3 x 4 x 1/4	3 x 4 x 1/4
Overall Width (in/cm)	80/203	92/234	80/203	92/234
Working Width (in/cm)	72/183	84/214	72/183	84/214
Working Depth (in/cm)	0-3.0/0-8	0-3.0/0-8	0-3.0/0-8	0-3.0/0-8
Max. Angle	20° L/R	20° L/R	20° L/R	20° L/R
Hydraulic Angle	Optional	Optional	Optional	Optional
Drive System	Hydraulic	Hydraulic	Hydraulic	Hydraulic
Rotor Drive	#80 Roller Chain	#80 Roller Chain	#80 Roller Chain	#80 Roller Chain
Chain Tensioner	Standard	Standard	Standard	Standard
Rotor Tooth	Carbide	Carbide	2" Sabre	2" Sabre
Gauge Wheel	Dual	Dual	Dual	Dual
Flip-up Side Shields	Standard	Standard	Standard	Standard
Material Control Bar	Adjustable	Adjustable	Adjustable	Adjustable
Weight (lbs/kg)	830/376	866/393	832/377	868/394
Product No.	360850	360855	360860	360865

65-Series Powered Landscape Rakes

Consistently delivering high performance, the 65-Series is designed for Skid Steers over 65 HP. It's rugged 4" x 4" x 1/4" frame supports dual flip-up gauge wheels (18.5 x 8.50-8) on 5-bolt hubs, flip-up side shields, adjustable material bar and environmentally dry chain case. A double #80 chain transfers the power to the rotor while chain tensioners of UMHW material provides the correct tension.

SPECIFICATIONS – 65-Series for Skid Steers over 65 HP

Model	PSHD-665	PSHD-765	PSHD-865	PSHD-665ST	PSHD-765ST	PSHD-865ST
Mount Type	Skid Steer	Skid Steer	Skid Steer	Skid Steer	Skid Steer	Skid Steer
Main Frame (in)	4 x 4 x 1/4	4 x 4 x 1/4	4 x 4 x 1/4	4 x 4 x 1/4	4 x 4 x 1/4	4 x 4 x 1/4
Overall Width (in/cm)	80/203	92/234	104/264	80/203	92/234	104/264
Working Width (in/cm)	72/183	84/214	96/244	72/183	84/214	96/244
Working Depth (in/cm)	0-3.0/0-8	0-3.0/0-8	0-3.0/0-8	0-3.0/0-8	0-3.0/0-8	0-3.0/0-8
Max. Angle	20° L/R	20° L/R	20° L/R	20° L/R	20° L/R	20° L/R
Hydraulic Angle	Optional	Optional	Optional	Optional	Optional	Optional
Drive System	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic
Rotor Drive	#80 Double Roller Chain	#80 Double Roller Chain	#80 Double Roller Chain	#80 Double Roller Chain	#80 Double Roller Chain	#80 Double Roller Chain
Chain Tensioner	Standard	Standard	Standard	Standard	Standard	Standard
Rotor Tooth	Carbide	Carbide	Carbide	2" Sabre	2" Sabre	2" Sabre
Gauge Wheel	Dual	Dual	Dual	Dual	Dual	Dual
Flip-up Side Shields	Standard	Standard	Standard	Standard	Standard	Standard
Material Control bar	Adjustable	Adjustable	Adjustable	Adjustable	Adjustable	Adjustable
Weight (lbs/kg)	1060/481	1105/501	1145/519	1062/482	1107/502	1147/520
Product No.	360570	360575	360580	360585	360590	360595

25-Series Powered Landscape Rakes

Get more done with a compact tractor when using one of our 25-Series Power Rakes designed for tractors of 24-40 HP. Standard equipment includes a #80 drive chain for dependable power transfer, PTO with slip clutch, dual flip-up gauge wheels, flip-up side shields for easy storage on the machine and adjustable material bar for controlling processed material flow.

SPECIFICATIONS – 25-Series for Tractors 24-40 HP

Model	PTC-525	PTC-625	PTC-725	PTC-525ST	PTC-625ST	PTC-725ST
Mount Type	3-pt Cat. I	3-pt Cat. I	3-pt Cat. I	3-pt Cat. I	3-pt Cat. I	3-pt Cat. I
Main Frame (in)	3 x 3 x 3/16	3 x 3 x 3/16	3 x 3 x 3/16	3 x 3 x 3/16	3 x 3 x 3/16	3 x 3 x 3/16
Overall Width (in/cm)	68/173	80/203	92/234	68/173	80/203	92/234
Working Width (in/cm)	60/152	72/183	84/214	60/152	72/183	84/214
Working Depth (in/cm)	0-3.0/0-8	0-3.0/0-8	0-3.0/0-8	0-3.0/0-8	0-3.0/0-8	0-3.0/0-8
Max. Angle	20° L/R	20° L/R	20° L/R	20° L/R	20° L/R	20° L/R
Hydraulic Angle	Optional	Optional	Optional	Optional	Optional	Optional
Drive System	PTO	PTO	PTO	PTO	PTO	PTO
Rotor Drive	#80 Roller Chain	#80 Roller Chain	#80 Roller Chain	#80 Roller Chain	#80 Roller Chain	#80 Roller Chain
Chain Tensioner	Standard	Standard	Standard	Standard	Standard	Standard
Rotor Tooth	Carbide	Carbide	Carbide	2" Sabre	2" Sabre	2" Sabre
Gauge Wheel	Dual	Dual	Dual	Dual	Dual	Dual
Flip-up Side Shields	Standard	Standard	Standard	Standard	Standard	Standard
Material Control Bar	Adjustable	Adjustable	Adjustable	Adjustable	Adjustable	Adjustable
Weight (lbs/kg)	755/343	790/358	825/374	757/343	792/359	827/375
Product No.	360800	360805	360810	360815	360820	360825

40-Series Powered Landscape Rakes

Providing ingenious solutions for your site prep needs, the 40-Series 3-pt mounted Power Rakes are matched to tractors of 35-75 HP. Standard features include PTO with slip clutch for sure power transfer, double #80 chain drive for long service life, rugged 4" x 4" x 1/4" frame, dual flip-up gauge wheel on 5-bolt hubs and heavy-duty adjustable material bar to control processed material flow.

SPECIFICATIONS – 40-Series for Tractors 35-75 HP

Model	PTHD-640	PTHD-740	PTHD-840	PTHD-640ST	PTHD-740ST	PTHD-840ST
Mount Type	3-pt Cat II	3-pt Cat II	3-pt Cat II	3-pt Cat II	3-pt Cat II	3-pt Cat II
Main Frame	4 x 4 x 1/4	4 x 4 x 1/4	4 x 4 x 1/4	4 x 4 x 1/4	4 x 4 x 1/4	4 x 4 x 1/4
Overall Width (in/cm)	80/203	92/234	104/264	80/203	92/234	104/264
Working Width (in/cm)	72/183	84/214	96/244	72/183	84/214	96/244
Working Depth (in/cm)	0-3.0/0-8	0-3.0/0-8	0-3.0/0-8	0-3.0/0-8	0-3.0/0-8	0-3.0/0-8
Max. Angle	20° L/R	20° L/R	20° L/R	20° L/R	20° L/R	20° L/R
Hydraulic Angle	Optional	Optional	Optional	Optional	Optional	Optional
Drive System	PTO	PTO	PTO	PTO	PTO	PTO
Rotor Drive	#80 Double Roller Chain	#80 Double Roller Chain	#80 Double Roller Chain	#80 Double Roller Chain	#80 Double Roller Chain	#80 Double Roller Chain
Chain Tensioner	Standard	Standard	Standard	Standard	Standard	Standard
Rotor Tooth	Carbide	Carbide	Carbide	2" Sabre	2" Sabre	2" Sabre
Gauge Wheel	Dual	Dual	Dual	Dual	Dual	Dual
Flip-up Side Shields	Standard	Standard	Standard	Standard	Standard	Standard
Material Control Bar	Adjustable	Adjustable	Adjustable	Adjustable	Adjustable	Adjustable
Weight (lbs/kg)	1065/483	1160/526	1255/569	1068/484	1162/527	1257/570
Product No.	360870	360875	360880	360885	360890	360895

Choose Worksaver For All Your Land Management

GENERAL IMPLEMENT DISTRIBUTORS

Worksaver

Power Rake Features

Flip-up Gauge Wheels (height adjustable) – Allows accurate control of working depth, keeping machine level for smoother surface finish. Operator can easily move the gauge wheels into the up position for transport on a trailer, reducing the space needed.

Flip-up Side Shields – Operator can easily move the shield out of the way for work where shields are not required. Shields are always with the machine, reducing the chance of misplacement.

Rotor Choice – Available with a carbide aggressor tooth (1-3/4") or 2" Sabre tooth (heat treated alloy material). Sabre tooth offers excellent reliability and performance for general use. Aggressor tooth offers more aggressive tilling action.

Dry Chain Case – Environmentally friendly dry chain case reduces maintenance as there is no oil to contend with. Chain only requires lubrication every 15-20 hours and is simply done by removing the chain case cover.

Heavy-Duty Chain – Chain is #60, #80 or double #80 depending on model. Chain size is matched to the machine for maximum power transfer. Tension is provided by serviceable chain tensioners of UMHW material for longer wear and reliability.

Adjustable Material Bar – Standard on all models for controlling processed material flow. Allows the operator to adjust to soil conditions increasing versatility of the unit.

Triple Seal Rotor Bearing with Replaceable Housing – Bearing housing of ductile material is replaceable, extending the life of the machine. Triple seal bearing keeps dirt out, providing more uptime.

Bearing Protectors – Standard on both sides of bearing on non-drive-end, or on rotor side of bearing on drive-end. Protects bearings from wrapping with material, thus increasing the service life of the bearings.

Lifting Point – Built-in lifting hook is standard on all machines for easier loading / unloading of machine.

Flex & Float System – Skid Steer units feature a "Flex & Float" mount. Allows the operator the flexibilty to choose maximum down pressure for preliminary site prep, then switch to float position for final site preparation.

GENERAL IMPLEMENT DISTRIBUTORS

Powered Landscape Rakes

Designed for Use on Mini / Compact Skid Steers.
Hydraulically Driven 10-Series, Standard Equipment includes, #80 Chain Drive, Flip-up Side Shields, 3"x 3"x 3/16" Frame, Two Flip-up Gauge Wheels, Adjustable Material Bar, hydraulic hoses w/ connect under pressure couplers

Product	Model	Item #	Description	Lbs.	List
	PXS-410	**360600**	4-ft Powered Landscape rake with Universal "mini" skid steer mount, manual angle (3-position), Carbide Aggressor rotor, side shields & two gauge wheels, hoses w/couplers	524	**11,004.00**
	PXS-510	**360605**	5-ft Powered Landscape rake with Universal "mini" skid steer mount, manual angle (3-position), Carbide Aggressor rotor, side shields & two gauge wheels, hoses w/couplers	560	**11,767.00**
	PXS-610	**360610**	6-ft Powered Landscape rake with Universal "mini" skid steer mount, manual angle (3-position), Carbide Aggressor rotor, side shields & two gauge wheels, hoses w/couplers	596	**12,705.00**
	PXS-410-ST	**360615**	4-ft Powered Landscape rake with Sabre Tooth rotor (2" composite metal tooth) Universal "mini" Skid Steer mount. Manual angle (3-position). Side shields & two gauge wheels, hoses w/ couplers std.	526	**10,234.00**
	PXS-510-ST	**360620**	5-ft Powered Landscape rake with Sabre Tooth rotor (2" composite metal tooth) Universal "mini" Skid Steer mount. Manual angle (3-position). Side shields & two gauge wheels, hoses w/ couplers std.	562	**10,976.00**
	PXS-610-ST	**360625**	6-ft Powered Landscape rake with Sabre Tooth rotor (2" composite metal tooth) Universal "mini" Skid Steer mount. Manual angle (3-position). Side shields & two gauge wheels, hoses w/ couplers std.	598	**11,893.00**

GENERAL IMPLEMENT DISTRIBUTORS

Powered Landscape Rakes

Options for 10-Series Power Landscape Rake					
Options					
	Side Shield Extensions	**360375**	Pair of Extensions mounts to side shield, for Model PXS-series		**196.00**
	Hyd. Angle kit	**360635**	Hydraulic angle kit for 10-series includes cylinder & hoses allowing use on power units with two sets of remotes.	22	**616.00**
	Hyd. Angle Kit w/ solenoid	**360640**	Hydraulic angle kit with solenoid for 10-series, includes cylinder & hoses allowing use on power units with only one remote	36	**1,484.00**
Powered Landscape Rake with alterative Mounts for 10-Series Machines.					
	Bobcat Mount	**360700**	PXS-410 with Bobcat MT Mount	540	**11,312.00**
		360705	PXS-510 with Bobcat MT Mount	576	**12,082.00**
		360715	PXS-610 with Bobcat MT Mount	612	**13,027.00**
		360720	PXS-410ST with Bobcat MT Mount	542	**10,549.00**
		360725	PXS-510ST with Bobcat MT Mount	578	**11,284.00**
		360730	PXS-610ST with Bobcat MT Mount	614	**12,201.00**

Worksaver®

Powered Landscape Rakes

Designed for Use on Skid Steers under 65 hp.
Hydraulically Driven, Standard Equipment includes, #80 Chain Drive, Flip-up Side Shields, 3" x 4" x ¼" Frame, Two Flip-up Gauge Wheels, Adjustable Material Bar, Hydraulic hoses w/ connect under pressure couplers, Universal Skid Steer Mount

Product	Model	Item #	Description	Lbs.	List
	PSS-620	**360850**	6-ft Powered Landscape rake with Universal skid steer mount, manual angle (3-position), Carbide Aggressor rotor, side shields & two gauge wheels, hoses w/couplers	830	**12,397.00**
	PSS-720	**360855**	7-ft Powered Landscape rake with Universal skid steer mount, manual angle (3-position), Carbide Aggressor rotor, side shields & two gauge wheels, hoses w/couplers	866	**13,321.00**
	PSS-620-ST	**360860**	6-ft Powered Landscape rake with Sabre Tooth rotor (2" composite metal tooth) Universal Skid Steer mount. Manual angle (3-position). Side shields & two gauge wheels, hoses w/couplers	832	**11,571.00**
	PSS-720-ST	**360865**	7-ft Powered Landscape rake with Sabre Tooth rotor (2" composite metal tooth) Universal Skid Steer mount. Manual angle (3-position). Side shields & two gauge wheels, hoses w/couplers	868	**12,516.00**
Options					
	Side Shield Extensions	360985	Pair of Extensions, mounts to side shield, for Model PSS-series	18	**196.00**
	Hyd. Angle Kit w/ Solenoid	360779	Hydraulic angle kit with solenoid for PSS-Series, includes cylinder & hoses allowing use on power units with only one remote	36	**2,135.00**

Electrical Wiring Kits for Skid Steers

To connect our electric / hydraulic solenoid control when installed on our Powered Rakes into OEM Skid Steer auxiliary electric controls allowing operating the electric / hydraulic solenoid valve from the operator seat with the buttons on the hand control.

GENERAL IMPLEMENT DISTRIBUTORS

Prices and Specifications may be subject to change without notice. Prices do not include shipping or setup.

Worksaver®

Powered Landscape Rakes

Heavy-Duty Design for Use on Skid Steers over 65 hp. Hydraulically Driven, Standard Equipment includes, Double #80 Chain Drive, Flip-up Side Shields, 4" x 4" x ¼" Frame, Two Flip-up Gauge Wheels, Adjustable Material Bar, Hydraulic hoses w/ connect under pressure couplers, Universal Skid Steer Mount					
Product	**Model**	**Item #**	**Description**	**Lbs.**	**List**
	PSHD-665	**360570**	6-ft HD-Powered Landscape rake with Universal skid steer mount, manual angle (3-position), Carbide Aggressor rotor, side shields & two gauge wheels, hoses w/couplers	1060	**14,203.00**
	PSHD-765	**360575**	7-ft HD- Powered Landscape rake with Universal skid steer mount, manual angle (3-position), Carbide Aggressor rotor, side shields & two gauge wheels, hoses w/couplers	1105	**14,959.00**
	PSHD-865	**360580**	8-ft HD- Powered Landscape rake with Universal skid steer mount, manual angle (3-position), Carbide Aggressor rotor, side shields & two gauge wheels, hoses w/couplers	1145	**16,086.00**
	PSHD-665-ST	**360585**	6-ft HD- Powered Landscape rake with Sabre Tooth rotor (2" composite metal tooth) Universal Skid Steer mount. Manual angle (3-position). Side shields & two gauge wheels, hose w/couplers	1065	**13,384.00**
	PSHD-765-ST	**360590**	7-ft HD-Powered Landscape rake with Sabre Tooth rotor (2" composite metal tooth) Universal Skid Steer mount. Manual angle (3-position). Side shields & two gauge wheels, hose w/couplers	1105	**14,126.00**
	PSHD-865-ST	**360595**	8-ft HD-Powered Landscape rake with Sabre Tooth rotor (2" composite metal tooth) Universal Skid Steer mount. Manual angle (3-position). Side shields & two gauge wheels, hose w/couplers	1145	**15,141.00**
Options					
	Side Shield Extensions	360985	Pair of Skid Shoes Mounts to side shield, for Model PSHD-series	18	**196.00**
	Hyd. Angle Kit w/ Solenoid	360864	Hyd. angle kit w/ solenoid for PSHD-Series (6' / 7'), includes cylinder & hoses use on power units with only one remote	59	**2,135.00**
	Hyd. Angle Kit w/ Solenoid	360866	Hyd. angle kit w/ solenoid for PSHD-Series (8'), includes cylinder & hoses use on power units with only one remote	60	**2,135.00**

Electrical Wiring Kits for Skid Steers

To connect our electric / hydraulic solenoid control when installed on our Powered Rakes into OEM Skid Steer auxiliary electric controls allowing operating the electric / hydraulic solenoid valve from the operator seat with the buttons on the hand control.

GENERAL IMPLEMENT DISTRIBUTORS

Prices and Specifications may be subject to change without notice. Prices do not include shipping or setup.

Powered Landscape Rakes

PTO Driven for Use on Tractors, 24 – 40 hp

PTO Driven (540 rpm), Standard Equipment includes, PTO w/ Slip Clutch, #80 Chain Drive, Flip-up Side Shields, Two Flip-up Gauge Wheels, Adjustable Material Bar, Manual Angle.

Fits Category I 3-pt

Product	Model	Item #	Description	Lbs.	List
	PTC-525	**360800**	5-ft PTO Powered Landscape rake 3-pt mount, manual angle (3-position), Carbide Aggressor rotor, side shields & two gauge wheels, slip clutch	755	**11,305.00**
	PTC-625	**360805**	6-ft PTO Powered Landscape rake 3-pt mount, manual angle (3-position), Carbide Aggressor rotor, side shields & two gauge wheels, slip clutch	790	**12,075.00**
	PTC-725	**360810**	7-ft PTO Powered Landscape rake 3-pt mount, manual angle (3-position), Carbide Aggressor rotor, side shields & two gauge wheels, slip clutch	825	**13,006.00**
	PTC-525-ST	**360815**	5-ft PTO Powered Landscape rake with Sabre Tooth rotor (2" composite metal tooth) Manual angle (3-position). Side shields & two gauge wheel, slip clutch	757	**10,500.00**
	PTC-625-ST	**360820**	6-ft PTO Powered Landscape rake with Sabre Tooth rotor (2" composite metal tooth) Manual angle (3-position). Side shields & two gauge wheels, slip clutch	792	**11,249.00**
	PTC-725-ST	**360825**	7-ft PTO Powered Landscape rake with Sabre Tooth rotor (2" composite metal tooth) Manual angle (3-position). Side shields & two gauge wheels, slip clutch	827	**11,907.00**
Options					
	Side Shield Extension	360985	Pair of Extensions Mounts to side shield, for Model PTC / PTHD-series	18	**196.00**
	Hyd. Angle Kit	360915	Hydraulic angle kit for PTC models, includes cylinder & hoses less couplers		**532.00**

Worksaver®

Powered Landscape Rakes

Heavy Duty Design for PTO Driven for Use on Tractors, 35-75 hp

PTO Driven (540 rpm), Standard Equipment includes, PTO w/ Slip Clutch, Double #80 Chain Drive, 4" x 4" x ¼" Frame, Flip-up Side Shields, Two Flip-up Gauge Wheels, Adjustable Material Bar, Manual Angle.

Fits Category I / II 3-pt

Product	Model	Item #	Description	Lbs.	List
	PTHD-640	**360870**	6-ft PTO Powered Landscape rake 3-pt mount, manual angle (3-position), Carbide Aggressor rotor, side shields & two gauge wheels, slip clutch	1065	**14,357.00**
	PTHD-740	**360875**	7-ft PTO Powered Landscape rake 3-pt mount, manual angle (3-position), Carbide Aggressor rotor, side shields & two gauge wheels, slip clutch	1160	**15,253.00**
	PTHD-840	**360880**	8-ft PTO Powered Landscape rake 3-pt mount, manual angle (3-position), Carbide Aggressor rotor, side shields & two gauge wheels, slip clutch	1255	**16,142.00**
	PTHD-640-ST	**360885**	6-ft PTO Powered Landscape rake with Sabre Tooth rotor (2" composite metal tooth) Manual angle (3-position). Side shields & two gauge wheel, slip clutch	1068	**13,552.00**
	PTHD-740-ST	**360890**	7-ft PTO Powered Landscape rake with Sabre Tooth rotor (2" composite metal tooth) Manual angle (3-position). Side shields & two gauge wheels, slip clutch	1162	**14,462.00**
	PTHD-840-ST	**360895**	8-ft PTO Powered Landscape rake with Sabre Tooth rotor (2" composite metal tooth) Manual angle (3-position). Side shields & two gauge wheels, slip clutch	1257	**15,232.00**
Options					
	Side Shield Extension	360985	Pair of Extensions Mounts to side shield, for Model PTC / PTHD-series	18	**196.00**
	Hyd. Angle Kit	360905	Hydraulic angle kit for PTHD models, includes cylinder & hoses less couplers		**532.00**

GENERAL IMPLEMENT DISTRIBUTORS

Prices and Specifications may be subject to change without notice. Prices do not include shipping or setup.