Worksaver

The widest choice of quality land management attachments.

Rotary Brooms

Designed for use by contractors, municipalities, institutions and farmers. Hydraulically driven models for skid steers, PTO driven models for 3-pt. tractor mounts (Cat.I). 32 inch diameter convoluted brushes available in Poly (P) or both Poly and Wire (PW). All models available in 5-ft., 6-ft., & 7-ft. widths.

- Remove dirt, sand, gravel and trash from construction entrances, parking lots, bridges, driveways & sidewalks.
- Remove thatch and prepare turf for the growing season.
- Clean snow or leaves from streets, driveways, and building entrances.
- Excellent for general clean up before sealing or repairing pavement.
- Brooms angle up to 30-degrees right or left. Optional manual or hydraulic angle adjustment kits available.
- Height adjustment chains maintain an even operating position.
- Parking stand included as standard equipment.

Skid Steer Rotary Broom

- Hydraulically driven skid steer models in 5-ft., 6-ft., & 7-ft.widths with 32" diameter brushes.
- Variable flow control valve for optimum broom speed.
- Step-through mount design for easy in/out of skid steer cab.
- Optional electric solenoid kit also offered.
- 4.36/1 chain drive ratio provides job matched torque to get through tough conditions.

3-pt. Rotary Broom

- PTO driven 3-pt. tractor mount in 5-ft., 6-ft., & 7-ft. widths with 32" diameter brushes.
- Double gearbox drive with patented top "T-shaft" for smooth power transmission and easy reversal of brush rotation.
- Designed for Category I tractors with 1,000 lbs. or greater 3-pt. lift capacity.

GENERAL IMPLEMENT DISTRIBUTORS

Skid Steer Rotary Broom Specifications

	SSMB-325P	SSMB-325PW	SSMB-326P	SSMB-326PW	SSMB-327P	SSMB-327PW
Overall Width (in/cm)	69 / 175	69 / 175	81 / 206	81 / 206	93 / 236	93 / 236
Brush Diameter (in/cm)	32 / 81	32 / 81	32 / 81	32 / 81	32 / 81	32 / 81
Sweeping Width (in/cm)	60 / 152	60 / 152	72 / 183	72 / 183	84 / 213	84 / 213
Width @ 30° Angle (in/cm)	53 / 135	53 / 135	64 / 163	64 / 163	76 / 193	76 / 193
Mounting System	Skid Steer	Skid Steer	Skid Steer	Skid Steer	Skid Steer	Skid Steer
Brush Material	Poly	Poly / Wire	Poly	Poly / Wire	Poly	Poly / Wire
Hydraulic Motor Rating	16 GPM	16 GPM	16 GPM	16 GPM	16 GPM	16 GPM
Oil Flow Requirement (gpm/lpm)	12-30 / 45-114	12-30 / 45-114	12-30 / 45-114	12-30 / 45-114	12-30 / 45-114	12-30 / 45-114
Dirt Deflector	Optional	Optional	Optional	Optional	Optional	Optional
Weight (lbs/kg)	640 / 290	637 / 289	740 / 336	736 / 334	840 / 381	833 / 378
Product No.	610961	610960	610966	610965	610971	610970

WARNING: Read and understand the operator's manual before operation. Be sure tractor/skid steer is properly counterbalanced. Damage to equipment or personal injury could occur.

3-pt. Rotary Broom Specifications

	RMB-325P	RMB-325PW	RMB-326P	RMB-326PW	RMB-327P	RMB-327PW
Overall Width (in/cm)	69 / 175	69 / 175	81 / 206	81 / 206	93 / 236	93 / 236
Brush Diameter (in/cm)	32 / 81	32 / 81	32 / 81	32 / 81	32 / 81	32 / 81
Sweeping Width (in/cm)	60 / 152	60 / 152	72 / 183	72 / 183	84 / 213	84 / 213
Width @ 30° Angle (in/cm)	53 / 135	53 / 135	64 / 163	64 / 163	76 / 193	76 / 193
Mounting System	3-pt. (Cat. I)	3-pt. (Cat. I)	3-pt. (Cat. I)	3-pt. (Cat. I)	3-pt. (Cat. I)	3-pt. (Cat. I)
Brush Material	Poly	Poly / Wire	Poly	Poly / Wire	Poly	Poly / Wire
PTO RPM Range	540	540	540	540	540	540
Dirt Deflector	Optional	Optional	Optional	Optional	Optional	Optional
Weight (lbs/kg)	720 / 326	714 / 324	780 / 354	774 / 351	840 / 381	833 / 378
Product No.	610705	610700	610755	610750	610805	610800

WARNING: Read and understand the operator's manual before operation. Be sure tractor/skid steer is properly counterbalanced. Damage to equipment or personal injury could occur.

Options

	Angle Adjustments Kits (all models require either a manual or hydraulic kit)
Product No. 610702	Manual Angle Adjustment Kit for either skid steers or 3-pt. tractor.
Product No. 610703	3-pt. Hydraulic Angle Adjustment Kit – includes cylinder & hoses less tips.
Product No. 610704	Skid Steer Hydraulic Angle Adjustment Kit – includes electric hydraulic solenoid control valve. For skid steer brooms used on units with only one set of remotes. Includes cylinder, hoses, valve, & flat-faced couplers. Factory installed.
	Electric Solenoid Kit (Optional)
Product No. 610950	Field installed electric hydraulic solenoid valve kit – fits product no. #610703 hydraulic angle kit above.

Choose Worksaver For All Your Land Management

GENERAL IMPLEMENT DISTRIBUTORS

Land Management Attachments

Rotary Brooms

Brooms angle 30-degrees right or left, and height adjustment chains maintain even operating position. Available in 32" diameter poly (P) or poly /wire (PW) combination. Parking stand standard. Either manual or hydraulic angle adjustment kit is required.

NOTE: For complete broom assembly, choose broom from Group I, and kit from Group 2 below.

Group 1 – Base Broom 3-pt Mount

PTO Driven Double Gearbox Drive

Product	Model	Item #	Description	Lbs.	List
	RMB-325P	610705	5-ft. Wide Poly Broom. Angle kit req. Cat. I Quick Hitch compatible.	640	7,672.00
	RMB-325PW	610700	5-ft. Wide Poly / Wire Broom. Angle kit req. Cat. I Quick Hitch compatible.	637	7,672.00
	RMB-326P	610755	6-ft. Wide Poly Broom. Angle kit req. Cat. I Quick Hitch compatible.	740	8,043.00
	RMB-326PW	610750	6-ft. Wide Poly / Wire Broom. Angle kit req. Cat. I Quick Hitch compatible	736	8,043.00
	RMB-327P	610805	7-ft. Wide Poly Broom. Angle kit req. Cat. I Quick Hitch compatible.	840	8,771.00
	RMB-327PW	610800	7-ft. Wide Poly / Wire Broom. Angle kit req. Cat. I Quick Hitch compatible	833	8,771.00

Group 1 -Skid Steer Mount Hydraulic Drive

Designed for skid steers and tractors with loaders that utilize the "universal" skid steer attaching system. Either manual or hydraulic angle adjustment kit is required. Optional gauge wheel kit is recommended.

	SSMB-325P	610961	5-ft. Wide Poly Broom. Angle kit req.	720	8,218.00
	SSMB-325PW	610960	5-ft. Wide Poly / Wire Broom. Angle kit required.	714	8,218.00
	SSMB-326P	610966	6-ft. Wide Poly Broom. Angle kit req.	780	8,750.00
	SSMB-326PW	610965	6-ft. Wide Poly / Wire Broom. Angle kit required.	774	8,750.00
	SSMB-327P	610971	7-ft. Wide Poly Broom. Angle kit req.	840	9,653.00
	SSMB-327PW	610970	7-ft. Wide Poly / Wire Broom. Angle kit required.	833	9,653.00
	Opt. Gauge Wheel Kit	610665	Gauge wheel kit allows setting the broom height to match the job conditions. Minimizing brush to ground contact.		616.00

Group 2 – Angle Adjustment Kit

Item #	Description	Lbs.	List
610702	Manual Angle Adjustment Kit	6	203.00
610703	Hydraulic Angle Adjustment Kit. Includes cylinder, hoses less tips. For use on tractor mounted 3-pt units.		637.00

Land Management Attachments

Rotary Brooms					
Universal Front Loader hydraulically driven brooms. Requires interfacing mounting brackets Available in 32” poly (P) or poly/wire (PW) combination. Either manual or hydraulic angle adjustment kit is required. Optional gauge wheel kit is recommended. **Note: For complete broom choose broom from Group 1 & Kit from Group 2**					
Group 1 - Front Loader Mount (requires additional brackets) (shipped less hoses)					
	ULMB-325P	610605	5-ft Universal front loader Poly Broom. Shipped less Brts. Optional bolt-on brackets available Angle kit required		7,721.00
	ULMB-325PW	610610	5-ft Universal front loader Poly/Wire Broom. Shipped less Brts. Optional bolt-on brackets available Angle kit req.		7,721.00
	ULMB-326P	610615	6-ft Universal front loader Poly Broom. Shipped less Brts. Optional bolt-on brackets available Angle kit required		8,260.00
	ULMB-326PW	610620	6-ft Universal front loader Poly/Wire Broom. Shipped less Brts. Optional bolt-on brackets available Angle kit required		8,260.00
	ULMB-327P	610625	7-ft Universal front loader Poly Broom. Shipped less Brts. Optional bolt-on brackets available Angle kit required		9,156.00
	ULMB-327PW	610630	7-ft Universal front loader Poly/Wire Broom. Shipped less Brts. Optional bolt-on brackets available Angle kit required		9,156.00
Group 1 -John Deere 400/500 series loader mount broom (shipped less hoses) Available in 32” poly (P) or poly/wire (PW) combination. Either manual or hydraulic angle adjustment kit is required. Optional gauge wheel kit is recommended. **(Group 2 kit required)**					
	JDMB-325P	610635	5-ft Poly Broom for John Deere 400/500 series loader. Angle kit req.		8,267.00
	JDMB-325PW	610640	5-ft Poly/Wire Broom for John Deere 400/500 series loader. Angle kit req.		8,267.00
	JDMB-326P	610645	6-ft Poly Broom for John Deere 400/500 series loader. Angle kit req.		8,792.00
	JDMB-326PW	610650	6-ft Poly/Wire Broom for John Deere 400/500 series loader. Angle kit req.		8,792.00
	JDMB-327P	610655	7-ft Poly Broom for John Deere 400/500 series loader. Angle kit req.		9,695.00
	JDMB-327PW	610660	7-ft Poly/Wire Broom for John Deere 400/500 series loader. Angle kit req.		9,695.00
	Opt. Gauge Wheel Kit	610665	Recommended for front loader brooms. Gauge wheel kit allows setting the broom height to match the job conditions. Minimizing brush to ground contact		616.00
Note: All broom prices include a well-built crate and can be stacked and shipped 2-high.					

Land Management Attachments

Group 2 – Angle Adjustment Kit			
Item #	**Description**	**Lbs.**	**List**
610702	Manual Angle Adjustment Kit	6	203.00
610703	Hydraulic Angle Adjustment Kit. Includes cylinder, hoses less tips. For use on tractor mounted 3-pt units.		637.00

Optional Broom Accessories			
610940	Hydraulic Angle Adjustment Kit with elec. hydraulic solenoid control. For skid steer rotary brooms used on units equipped with only one set of remotes. Includes cylinder, hoses, valve, & flat-faced couplers. **Factory installed.**	55	2,044.00
Field Installed Hydraulic Kit			
610950	Field Installed Hydraulic Angle Adjustment Kit with elec. hydraulic solenoid control. For skid steer rotary brooms used on units equipped with only one set of remotes. Includes cylinder, hoses, valve, & flat-faced couplers..	55	2,079.00
Optional Gauge Wheel kit for Rotary Brooms. Gauge wheels allow the operator to set and maintain proper sweeping height			
610665	Dual Gauge wheel kit for all rotary broom models		616.00

Electrical Wiring Kits for Skid Steers To connect our electric / hydraulic solenoid control when installed on our Rotary Brooms (or Power Landscape Rakes) into OEM Skid Steer auxiliary electric controls allowing operating the electric / hydraulic solenoid valve from the operator seat with the buttons on the hand control.			
2507024	ASV Skid Steer 8 Pin Wiring Kit	2	434.00
2507026	Bobcat Skid Steer 14 Pin Wiring Kit	2	434.00
2507027	Case Skid Steer 14 Pin Wiring Kit	2	434.00
2507024	Caterpillar Skid Steer 8 Pin Wiring Kit	2	434.00
2507028	Caterpillar Skid Steer 14 Pin Wiring Kit	2	434.00
TBA	Gehl Skid Steer 14 Pin Wiring Kit	2	TBA
2507029	JCB Skid Steer 14 Pin Wiring Kit	2	434.00
2507030	John Deere Skid Steer 14 Pin Wiring Kit	2	434.00
2507031	Kubota Skid Steer 14 Pin Wiring Kit	2	434.00
2507027	New Holland Skid Steer 14 Pin Wiring Kit	2	434.00
TBA	Mustang Skid Steer 14 Pin Wiring Kit		TBA
2507029	Volo Skid Steer 14 Pin Wiring Kit	2	434.00
2507031	Wacker Neuson Skid Steer 14 Pin Wiring Kit	2	434.00