



*WorkSaver.*

*Designed.  
Engineered.  
Remarkable  
Value.*

## Model CS-694, CS-1094 Spreaders

Available in six or ten bushel capacity to meet all your spreading requirements.



Choice of (3) Spread Patterns

# Worksaver Model CS-694, CS-1094

## MODEL CS-694 SPECIFICATIONS

Capacity .....	Six (6) bu. (500 lb.)
Hopper construction .....	Steel
Main frame construction .....	Tubular Steel
O.D. size of steel tubing (in/mm) .....	2-3/8 / (60mm)
Drive system .....	Tractor PTO
PTO driveline .....	Metric Series I
PTO speed .....	540 rpm
Fully shield drive .....	Standard
Spreader drive .....	PTO / Gear Box
Spreader patterns .....	Left, Center, Right
Hitch requirement .....	Cat. I (7/8" Dia. Lift pins)
Shipping weight (lb./kg) .....	110 / (50 kg)
Product Computer Number .....	420700

## MODEL CS-1094 SPECIFICATIONS

Capacity .....	Ten (10) bu. (800 lb.)
Hopper construction .....	Steel (CS-1094)
Main frame construction .....	Tubular Steel
O.D. size of steel tubing (in/mm) .....	2-3/8 / (60mm)
Drive system .....	Tractor PTO
PTO driveline .....	Metric Series I
PTO speed .....	540 rpm
Fully shield drive .....	Standard
Spreader drive .....	PTO / Gear Box
Spreader patterns .....	Left, Center, Right
Hitch requirement .....	Cat. I (7/8" Dia. Lift pins)
Shipping weight (lb./kg) (Steel Hopper).....	122 / (55 kg)
Product Computer Number .....	420800 (CS-1094)


- Choice of (3) spread patterns.
- Adjustable spinner fins.
- Accurate broadcasting of grass seed, wheat or fertilizer.
- PTO operated for optimum performance.
- Fits Category I three-point hitches.
- Tubular steel main frame.
- Optional rotating wheel agitator for lime.
- Symmetric spreading for optimum overlap.
- Cone shaped hopper provides easy material flow.



READ AND UNDERSTAND OPERATOR'S MANUAL BEFORE OPERATION.

Worksaver Inc. has a corporate policy of continuous product improvement and development; therefore, specifications are subject to change without any advance notice. Worksaver Inc. is not responsible for differences between specifications or illustrations contained in this publication and the actual equipment.

## Acreage Attachments

<b>Seeders / Spreaders – PTO Driven</b>					
Tractor 3-pt mounted Cat I w/ 7/8" pins					
Product	Model	Item #	Description	Lbs.	List
	CS-694	420700	6-bushel steel cone PTO Seeder / Spreader. Designed for standard tractors Holds approximately 480 lbs.	110	1,043.00
	CS-1094	420800	10-bushel steel cone PTO Seeder / Spreader. Designed for standard tractors. Holds approximately 900 lbs.	122	1,120.00
		420725	Optional wheel-type lime agitator for CS-series cone seeders	3	105.00